

## IP Camera

NO.	Model   Appearance	Specification	Price (IRR)
1	  <b>DH-IPC-PDBW8840-A180</b> <i>Wiz Mind</i>	<p>“4x2MP WizMind Multi-Sensor Panoramic Dome Network Camera”</p> <ul style="list-style-type: none"> <li>Four 2MP 1/2.8" CMOS image sensor, low illuminance, high image definition</li> <li>Outputs max. 8MP (4096 × 1800) @30 fps</li> <li>Built-in IR LED, max. IR distance: 30 m</li> <li>ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments</li> <li><b>Intelligent functions:</b> Crowd distribution map, Vehicle Density</li> <li><b>Abnormality detection:</b> Motion detection, video tampering, scene changing, audio detection, no SD card SD card full, SD card error, network disconnection, IP conflict, illegal access, and voltage detection</li> <li><b>Alarm:</b> 2 in, 2 out; audio: 1 in, 1 out; 485; BNC; supports max. 256 G SD card</li> <li>12V DC/24V AC/PoE power supply; easy for installation</li> <li>Supports object tracking</li> <li>IP67,IK10 protection</li> <li>tripwire ;intrusion</li> </ul> <p> دوکان مداربسته تحت شبکه داهوا مدل DH-IPC-PDBW8840-A180</p>	CALL
2	  <b>DH-IPC-PFW8840-A180</b> <i>Wiz Mind</i>	<p>“4x2MP WizMind Multi-Sensor Panoramic Network IR Bullet Camera”</p> <ul style="list-style-type: none"> <li>Four 2MP 1/2.8" CMOS image sensor, low illuminance, high image definition</li> <li>Outputs max. 8MP (4096 × 1800) @30 fps</li> <li>H.265 codec, high compression rate, ultra-low bit rate</li> <li>Built-in IR LED, max. IR distance: 30 m</li> <li>ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments</li> <li>DWDR, 3D NR, HLC, BLC, digital watermarking</li> <li><b>Intelligent functions:</b> Crowd distribution map, Vehicle Density situation</li> <li><b>Abnormality detection:</b> Motion detection, video tampering, scene changing, audio detection, no SD card SD card full, SD card error, network disconnection, IP conflict, illegal access, and voltage detection</li> <li><b>Alarm:</b> 2 in, 2 out; audio: 1 in, 1 out; 485; BNC; supports max. 256 G SD card</li> <li>12V DC/24V AC/PoE power supply; easy for installation</li> <li>Supports object tracking</li> <li>IP67, IK10 protection</li> <li>tripwire ;intrusion</li> </ul> <p> دوکان مداربسته تحت شبکه داهوا مدل DH-IPC-PFW8840-A180</p>	CALL

NO.	Model   Appearance	Specification	Price (IRR)
3	 <b>DH-PSDW8842ML-A180-D237</b> <i>Wiz Mind</i>	<p>“4x2MP Multi-Sensor Panoramic + PTZ WizMind Network Camera”</p> <ul style="list-style-type: none"> <li>Panoramic: Four 1/1.8" 2 Megapixel progressive scan CMOS</li> <li>Main stream(4096×1800@1~30fps),Sub Stream(1024×452@1~30fps),Third Stream(1920×832@`~30fps)</li> <li>PTZ: One 1/1.8" 2 Megapixel progressive scan CMOS</li> <li>Main stream(1920×1080@1~30fps),Sub Stream(704×480@1~30fps),Third Stream(1280×720@1~30fps)</li> <li>Support 180-degree panoramic view</li> <li>Starlight+ technology</li> <li>Support Smart H265+/H264+ encoding</li> <li>Day/Night (ICR); 3D NR; AWB; AGC; BLC</li> <li>IR distance up to 220 m</li> <li>Smart tracking</li> <li>Tripwire,Intrusion</li> </ul>	CALL
4	 <b>DH-IPC-HFW7442HP-ZVH</b> <i>Wiz Mind</i>  	<p>“4MP IR Bullet WizMind Network Camera”</p> <ul style="list-style-type: none"> <li>4MP, 1/1.8" CMOS image sensor, low illuminance, high definition image.</li> <li>Max outputs 4MP (2688 × 1520) @50 fps/60 fps.</li> <li>H.264/H.265 coding, high compression ration.</li> <li>Wide dynamic,day/night, 3D NR, AWB, HLC, BLC.</li> <li>ROI, SVC, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments.</li> <li>With deep learning algorithm, it supports ANPR, parking Space management, video metadata, perimeter protection.</li> <li><b>Alarm:</b> 3 in, 2 out; audio: 1 in, 1 out; RS-485; BNC; supports max. 256 G SD card</li> <li>24 VAC 12 VDC/PoE power supply (the power ports are different depending on the power supply)</li> <li>Five streams for three-channel HD video</li> <li>IP67, IK10 protection grade</li> <li>Anti-corrosion coating(optional)</li> <li>12 VDC power output, max. current 165mA , easy for installation</li> </ul>	CALL

NO.	Model   Appearance	Specification	Price (IRR)
5	 <b>DH-IPC-ITC237-PW1B-IRZ</b> 	<p>“2 Megapixel Full HD WDR Access ANPR Camera”</p> <ul style="list-style-type: none"> <li>• Embedded with LPR algorithm inside the camera.</li> <li>• Support plate cutout, overview picture snapshot and video recording</li> <li>• Embedded with White list database, control the barrier</li> <li>• Powerful 2.7-12mm motorized lens and IR light, ideal for monitor ANPR distance as 3~8m</li> <li>• Wide working temperature, IP67, IK10 and superior performance for outdoor applications</li> <li>• True WDR technology</li> <li>• 25/30fps@1080P(1920×1080), 2.7mm~12mm Motorize lens</li> <li>• WDR(140dB), BLC, HLC, Day/Night(ICR), 3DNR, AWB, AGC, BLC</li> <li>• 1/2.8" 2Megapixel progressive scan CMOS</li> <li>• 265/H.264M/H.264H/H.264B dual-stream encoding</li> <li>• 25/30fps@1080P(1920×1080), 2.7mm~12mm Motorize lens</li> <li>• WDR(140dB), BLC, HLC, Day/Night(ICR), 3DNR, AWB, AGC, BLC</li> <li>• Mirco SD card 64GB, IR Distance 3~8m, IP67, IK10, PoE</li> </ul>	138,600,000
6	 <b>DH-IPC-ITC237-PW6M</b> 	<p>“2MP Long Range Access ANPR Camera”</p> <ul style="list-style-type: none"> <li>• 1/1.8" 2Megapixel GS-CMOS image sensor</li> <li>• H.265/H.264M/H.264H/H.264B dual-stream encoding</li> <li>• 25/30fps@1080P(1920×1080), 10mm~50mm Motorize Varifocal lens</li> <li>• WDR(96dB), BLC, HLC, Day/Night(ICR), 3DNR, AWB, AGC, BLC</li> <li>• Vehicle Detection, Vehicle Recognition, Video Metadata Support</li> <li>• Built-in LED illuminator, 25m Max Illumination Distance</li> <li>• Mirco SD card 64GB</li> <li>• IP67, IK10, PoE</li> </ul>	<span style="color: red;">CALL</span>

 DH-IPC-ITC237-PW6M دوربین مداربسته تحت شبکه داهوا مدل

NO.	Model   Appearance	Specification	Price (IRR)
7	  <b>DH-IPC5831EP-ZE</b>	<p><b>"8MP WDR IR Bullet Network Camera"</b></p> <ul style="list-style-type: none"> <li>• 1/2.5" 8 Megapixel progressive scan STARVIS™ CMOS</li> <li>• H.265+/H.265/H.264+/H.264 Triple-stream encoding</li> <li>• 15fps@4K(3840×2160), 25/30fps@3Mp(2304×1296)</li> <li>• 2.7mm ~12mm motorized lens, Max. Aperture F1.4</li> <li>• WDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC</li> <li>• Micro SD card memory , 128 GB, 1/1 Audio In/Out, 2/1 Alarm In/Out</li> <li>• Max. IR LEDs Length 50m , Smart IR, IP67,IK10, PoE</li> <li>• (Tripwire Intrusion Object Abandoned/Missing Face)</li> </ul>	103,950,000
8	  <b>DH-IPC-HFW5442EP-ZE</b> <i>Wiz Mind</i> 	<p><b>"4MP IR Vari-focal Bullet WizMind Network Camera"</b></p> <ul style="list-style-type: none"> <li>• 4-MP 1/1.8" CMOS image sensor, low luminance, and high definition image.</li> <li>• Outputs max. 4 MP (2688 × 1520)@30 fps.</li> <li>• Built-in IR LED, and the max. illumination distance is 60 m.</li> <li>• ROI, SVC, SMART H.264+/H.265+, AI H.264/H.265, encoding after filter, flexible coding, applicable to various bandwidth and storage environments.</li> <li>• Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes.</li> <li>• Alarm: 2 in, 1 out; audio: 1 in, 1 out; supports max. 256 G Micro SD card.</li> <li>• 12 VDC/PoE power supply, easy for installation.</li> <li>• IP67 and IK10 protection; ePoE.</li> <li>• SMD 3.0.</li> </ul>	112,350,000

NO.	Model   Appearance	Specification	Price (IRR)
9	 <b>DH-IPC-HFW5241EP-Z5E</b> <i>Wiz Mind</i> ePoE	<p>“2MP IR Vari-focal Bullet WizMind Network Camera”</p> <ul style="list-style-type: none"> <li>• 2-MP 1/2.8" CMOS image sensor, low luminance, and high definition image.</li> <li>• Outputs max. 2 MP (1920 × 1080)@30 fps.</li> <li>• H.265 codec, high compression rate, ultra-low bit rate.</li> <li>• Built-in IR LED, and the max. illumination distance is 130 m.</li> <li>• ROI, SVC, SMART H.264+/H.265+, AI H.264/H.265, encoding after filter, flexible coding, applicable to various bandwidth and storage environments.</li> <li>• Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes.</li> <li>• Three switchable intelligent resources: IVS, face detection, and people counting.</li> <li>• Alarm: 2 in, 1 out; audio: 1 in, 1 out; supports max. 256 G Micro SD card.</li> <li>• 12 VDC/PoE power supply, easy for installation.</li> <li>• IP67 and IK10 protection; ePoE.</li> <li>• SMD3.0.</li> </ul> <div style="display: flex; align-items: center;">  DH-IPC-HFW5241EP-Z5E دویین مداربسته تحت شبکه داهوا مدل         </div>	95,000,000
10	 <b>DH-IPC-HFW5241TP-ASE-NI</b> <i>ePoE</i>	<p>“2MP Pro AI Full-color Fixed-focal Bullet Network Camera”</p> <ul style="list-style-type: none"> <li>• 2MP, 1/2.8" CMOS image sensor, low illuminance, high image definition</li> <li>• Outputs max. 2MP (1920 × 1080)@30 fps</li> <li>• H.265 codec, high compression rate, low bit rate</li> <li>• ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments</li> <li>• Rotation mode, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes</li> <li>• <b>Intelligent detection:</b> Tripwire, intrusion, fast moving (the three functions support the classification and accurate detection of vehicle and human), abandoned object, missing object, loitering detection, people gathering, parking detection, heat map, and face detection.</li> <li>• <b>Abnormality detection:</b> Motion detection, video tampering, scene changing, audio detection, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, voltage detection</li> <li>• Alarm: 1 in, 1 out; Audio: 1 in, 1 out; supports max. 256 G Micro SD card</li> <li>• 12V DC/PoE power support</li> <li>• ePoE for remote transmission</li> <li>• IP67 protection</li> </ul> <div style="display: flex; align-items: center;">  DH-IPC-HFW5241TP-ASE-NI دویین مداربسته تحت شبکه داهوا مدل         </div>	89,000,000

NO.	Model   Appearance	Specification	Price (IRR)
11	 <b>DH-IPC-HFW5231EP-ZE</b>	<p>“2MP WDR IR Bullet Network Camera”</p> <ul style="list-style-type: none"> <li>• 1/2.8" 2Megapixel progressive scan STARVIS™ CMOS</li> <li>• H.265&amp;H.264 triple-stream encoding</li> <li>• 50/60fps@1080(1920×1080)</li> <li>• Smart Detection supported</li> <li>• WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC</li> <li>• Multiple network monitoring: Web viewer, CMS(DSS/PSS) &amp; DMSS</li> <li>• 2.7mm ~13.5mm motorized lens</li> <li>• 2/1 Alarm in/out, 1/1 audio in/out</li> <li>• Max. IR LEDs Length 50m</li> <li>• Micro SD memory, IP67, IK10, PoE</li> </ul>	85,000,000
12	 <b>DH-IPC-HFW4831TP-ASE</b> <span style="color: red;">()</span>	<p>4K</p> <p>“8MP WDR IR Mini Bullet Network Camera”</p> <ul style="list-style-type: none"> <li>• 1/2.5" 8Megapixel progressive scan STARVISTM CMOS</li> <li>• H. 265&amp;H.264 triple-stream encoding</li> <li>• 15fps@4K(3840×2160),25/30fps@3M(2304×1296)</li> <li>• Smart Detection supported</li> <li>• WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC</li> <li>• Multiple network monitoring: Web viewer, CMS(DSS/PSS) &amp; DMSS</li> <li>• 2.8mm fixed lens (4mm optional)</li> <li>• Max. IR LEDs Length 80m</li> <li>• Micro SD Memory,IP67, IK10, PoE</li> </ul>	82,000,000

 DH-IPC-HFW4831TP-ASE دویرین مداربسته تحت شبکه داهوا مدل

NO.	Model   Appearance	Specification	Price (IRR)
13	 <b>DH-IPC-HFW4431EP-Z</b>	<p>“4MP WDR IR Bullet Network Camera”</p> <ul style="list-style-type: none"> <li>• 1/3" 4Megapixel progressive scan CMOS</li> <li>• H.265&amp;H.264 triple-stream encoding</li> <li>• 25/30fps@4Mp(2688×1520)</li> <li>• Smart Detection supported</li> <li>• WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC</li> <li>• Multiple network monitoring: Web viewer, CMS(DSS/PSS) &amp; DMSS</li> <li>• 2.7mm ~13.5mm motorized lens</li> <li>• 2/1 Alarm in/out, 1/1 audio in/out</li> <li>• Max. IR LEDs Length 50m</li> <li>• Micro SD memory 256GB, IP67, IK10, PoE</li> </ul>	77,000,000
14	 <b>DH-IPC-HFW4831EP-SE</b>	<p>“8MP WDR IR Mini Bullet Network Camera”</p> <ul style="list-style-type: none"> <li>• 1/2.5" 8Megapixel progressive scan STARVIS™ CMOS</li> <li>• H.265&amp;H.264 triple-stream encoding</li> <li>• 15fps@4K(3840×2160), 25/30fps@3M(2304×1296)</li> <li>• Smart Detection supported</li> <li>• WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC</li> <li>• Multiple network monitoring: Web viewer, CMS(DSS/PSS) &amp; DMSS</li> <li>• 2.8mm fixed lens (4mm optional)</li> <li>• Max. IR LEDs Length 40m</li> <li>• Micro SD Memory, IP67, PoE</li> </ul>	62,800,000

[DH-IPC-HFW4831EP-SE دویرین مداربسته تحت شبکه داهوا مدل](#)

NO.	Model   Appearance	Specification	Price (IRR)
15	 <b>DH-IPC-HFW3849T1P-AS-PV</b> <span>Full-Color</span>	<p>“8MP Full-color Active Deterrence Fixed-focal Bullet WizSense Network Camera”</p> <ul style="list-style-type: none"> <li>• 8MP, 1/2.8" CMOS image sensor, low illuminance, high image definition</li> <li>• Outputs max. 8MP (3840 × 2160) @20 fps (AI function enabled by default) and supports 8MP (3840 × 2160) @25/30 fps (with AI function disabled) • H.265 codec, high compression rate, low bit rate</li> <li>• Built-in warm illuminator, and the max. illumination distance: 30 m</li> <li>• ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments</li> <li>• Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes</li> <li><b>Intelligent detection:</b> Tripwire, intrusion (the three functions support the classification and accurate detection of vehicle and human)</li> <li><b>Abnormality detection:</b> Motion detection, video tampering, scene changing, audio detection, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, and voltage detection</li> <li>• Supports sound and light alarm linkage. When an alarm is triggered, the camera links sound alarm and light flashing</li> <li>• Supports one-tap disarming. You can disarm the events of alarm output, sending email, audio, and light in the configured period</li> <li><b>Alarm:</b> 1 in, 1 out; audio: 1 in, 1 out; supports max. 256 G Micro SD card, built-in Mic and speaker</li> <li>• 12V DC/PoE power supply • IP67 protection</li> <li>• SMD Plus • Red and blue flashlight alarm</li> </ul> <p> <a href="#">دربیین مداربسته تحت شبکه داهوا مدل DH-IPC-HFW3849T1P-AS-PV</a></p>	89,000,000
16	 <b>DH-IPC-HFW3449T1P-AS-PV</b> <span>Full-Color</span>	<p>“4MP Full-color Active Deterrence Fixed-focal Bullet WizSense Network Camera”</p> <ul style="list-style-type: none"> <li>• 4MP, 1/2.7" CMOS image sensor, low illuminance, high image definition</li> <li>• Outputs max. 4MP (2688 × 1520) @30 fps</li> <li>• H.265 codec, high compression rate, low bit rate</li> <li>• Built-in warm illuminator, and the max. illumination distance: 40 m</li> <li>• ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments</li> <li>• Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes</li> <li><b>Intelligent detection:</b> Intrusion, tripwire (support the classification and accurate detection of vehicle and human)</li> <li><b>Abnormality detection:</b> Motion detection, video tampering, scene changing, audio detection, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, and voltage detection.</li> <li>• Supports sound and light alarm linkage. When an alarm is triggered, the camera links sound alarm and light flashing.</li> <li>• Supports one-tap disarming. You can disarm the events of alarm output, sending email, audio, and light in the configured period.</li> <li><b>Alarm:</b> 1 in, 1 out; audio: 1 in, 1 out; supports max. 256 G Micro SD card, built-in Mic and speaker</li> <li>• 12V DC/PoE power supply</li> <li>• IP67 protection</li> <li>• SMD Plus</li> <li>• Red and blue flashlight alarm</li> </ul> <p> <a href="#">دربیین مداربسته تحت شبکه داهوا مدل DH-IPC-HFW3449T1P-AS-PV</a></p>	80,000,000

NO.	Model   Appearance	Specification	Price (IRR)
17	<p>Full-Color</p>  <p><b>DH-IPC-HDW3449HP-AS-PV</b> ⌚ Wiz Sense</p>	<p>“4MP Full-color Active Deterrence Fixed-focal Eyeball WizSense Network Camera”</p> <ul style="list-style-type: none"> <li>• 4MP, 1/2.7" CMOS image sensor, low illuminance, high image definition</li> <li>• Outputs max. 4MP (2688 × 1520) @30 fps</li> <li>• H.265 codec, high compression rate, low bit rate</li> <li>• Built-in warm illuminator, and the max. illumination distance: 30 m</li> <li>• ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments</li> <li>• Rotation mode, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes</li> <li>• <b>Intelligent detection:</b> Intrusion, tripwire (support the classification and accurate detection of vehicle and human)</li> <li>• <b>Abnormality detection:</b> Motion detection, video tampering, scene changing, audio detection, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, and voltage detection.</li> <li>• Supports sound and light alarm linkage. When an alarm is triggered, the camera links sound alarm and light flashing.</li> <li>• Supports one-tap disarming. You can disarm the events of alarm output, sending email, audio, and light in the configured period.</li> <li>• <b>Alarm:</b> 1 in, 1 out; audio: 1 in, 1 out; supports max. 256 G Micro SD card, built-in Mic and speaker</li> <li>• 12V DC/PoE power supply</li> <li>• IP67 protection</li> <li>• SMD Plus</li> <li>• Red and blue flashlight alarm</li> </ul> <p>دروبین مداربسته تحت شبکه داهوا مدل DH-IPC-HDW3449HP-AS-PV</p>	59,000,000
18	<p>Full-Color</p>  <p><b>DH-IPC-HDW3449TMP-AS-LED</b> ⌚ Wiz Sense</p>	<p>“4MP Full-color Warm LED Fixed-focal Eyeball WizSense Network Camera”</p> <ul style="list-style-type: none"> <li>• 4MP, 1/2.7" CMOS image sensor, low illuminance, high image definition</li> <li>• Outputs max. 4MP (2688 × 1520) @ 30 fps</li> <li>• H.265 codec, high compression rate, low bit rate</li> <li>• Built-in Warm LED, max. LEDs distance: 30 m</li> <li>• ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments</li> <li>• Rotation mode, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes</li> <li>• <b>Intelligent detection:</b> Intrusion, tripwire (support the classification and accurate detection of vehicle and human)</li> <li>• <b>Abnormality detection:</b> Motion detection, video tampering, scene changing, audio detection, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, voltage detection</li> <li>• Supports max. 256 G Micro SD card, built-in Mic</li> <li>• 12V DC/PoE power support</li> <li>• IP67 protection</li> <li>• SMD Plus</li> </ul> <p>دروبین مداربسته تحت شبکه داهوا مدل DH-IPC-HDW3449TMP-AS-LED</p>	52,000,000

NO.	Model   Appearance	Specification	Price (IRR)
19	  <b>DH-IPC-HFW3449EP-SA-LED</b> <span style="color:red;">⌚ Wiz Sense</span>	<p>“4MP Full-color Warm LED Fixed-focal Bullet WizSense Network Camera”</p> <ul style="list-style-type: none"> <li>• 4MP, 1/2.7" CMOS image sensor, low illuminance, high image definition</li> <li>• Outputs max. 4MP (2688 × 1520) @ 30 fps</li> <li>• H.265 codec, high compression rate, low bit rate</li> <li>• Built-in Warm LED, max. LED distance: 30 m</li> <li>• ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments</li> <li>• Rotation mode, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes</li> <li>• <b>Intelligent detection:</b> Intrusion, tripwire (support the classification and accurate detection of vehicle and human)</li> <li>• <b>Abnormality detection:</b> Motion detection, video tampering, scene changing, audio detection, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, voltage detection</li> <li>• <b>Alarm:</b> 1 in, 1 out; audio: 1 in, 1 out; supports max. 256 G Micro SD card, built-in Mic</li> <li>• 12V DC/PoE power support</li> <li>• IP67 protection</li> <li>• SMD Plus</li> </ul> <p> دویرین مداربسته تحت شبکه داهوا مدل DH-IPC-HFW3449EP-SA-LED</p>	52,000,000
20	  <b>DH-IPC-HFW3441EP-SA</b> <span style="color:red;">⌚ Wiz Sense</span>	<p>“4MP IR Fixed focal Bullet WizSense Network Camera”</p> <ul style="list-style-type: none"> <li>• 4MP, 1/3" CMOS image sensor, low illuminance, high image definition</li> <li>• Outputs max. 4MP (2688 × 1520) @ 30 fps</li> <li>• H.265 codec, high compression rate, low bit rate</li> <li>• Built-in IR LED, max. IR distance: 50 m</li> <li>• ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments</li> <li>• Rotation mode, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes</li> <li>• <b>Intelligent detection:</b> Intrusion, tripwire (support the classification and accurate detection of vehicle and human)</li> <li>• <b>Abnormality detection:</b> Motion detection, video tampering, scene changing, audio detection, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, voltage detection</li> <li>• Supports max. 256 G Micro SD card • built-in Mic</li> <li>• 12V DC/POE power supply</li> <li>• IP67 protection</li> <li>• SMD Plus</li> </ul> <p> دویرین مداربسته تحت شبکه داهوا مدل DH-IPC-HFW3441EP-SA</p>	44,500,000

NO.	Model   Appearance	Specification	Price (IRR)
21	  <b>DH-IPC-HDW3441TMP-AS</b> <span style="color: red;">⌚ Wiz Sense</span>	<p>“4MP IR Fixed focal Eyeball WizSense Network Camera”</p> <ul style="list-style-type: none"> <li>• 4MP, 1/3" CMOS image sensor, low illuminance, high image definition</li> <li>• Outputs max. 4MP(2688 × 1520) @30 fps</li> <li>• H.265 codec, high compression rate, low bit rate</li> <li>• Built-in IR LED, max. IR distance: 50 m</li> <li>• ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments</li> <li>• Rotation mode, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes</li> <li>• <b>Intelligent detection:</b> Intrusion, tripwire (support the classification and accurate detection of vehicle and human)</li> <li>• <b>Abnormality detection:</b> Motion detection, video tampering, scene changing, audio detection, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, voltage detection</li> <li>• Supports max. 256 G Micro SD card • built-in Mic</li> <li>• 12V DC/POE power supply</li> <li>• IP67 protection</li> <li>• SMD Plus</li> </ul> <p> DH-IPC-HDW3441TMP-AS دویرین مداربسته تحت شبکه داهوا مدل</p>	44,500,000
22	 <b>DH-IPC-HFW2831TP-ZAS-S2</b>	<p>“8MP Lite IR Vari-focal Bullet Network Camera”</p> <ul style="list-style-type: none"> <li>• 8MP, 1/2.7" CMOS image sensor, low illuminance, high image definition</li> <li>• H.265&amp;H.264 triple-stream encoding</li> <li>• Outputs max. 8MP(3840 × 2160) @15 fps, and supports 2688 × 1520 (2688 × 1520) @25/30 fps</li> <li>• H.265 codec, high compression rate, ultra-low bit rate</li> <li>• ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments</li> <li>• Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes</li> <li>• Intelligent detection: Intrusion, tripwire</li> <li>• Abnormality detection: Motion detection, video tampering, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, local alarm, voltage detection, audio abnormal</li> <li>• Alarm: 1 in, 1 out; audio: 1 in, 1 out; supports max. 256 GB Micro SD card</li> <li>• 12V DC/PoE power supply</li> <li>• IP67 protection</li> </ul> <p> DH-IPC-HFW2831TP-ZAS-S2 دویرین مداربسته تحت شبکه داهوا مدل</p>	78,000,000

NO.	Model   Appearance	Specification	Price (IRR)
23	 <b>DH-IPC-HFW2831TP-AS-S2</b> 🔊	<p>“8MP Lite IR Fixed-focal Bullet Network Camera”</p> <ul style="list-style-type: none"><li>• 8MP, 1/2.7" CMOS image sensor, low illuminance, high image definition</li><li>• Outputs max. 8MP (3840 × 2160) @15 fps, and supports 2688×1520 (2688 × 1520) @25/30 fps</li><li>• H.265 codec, high compression rate, ultra-low bit rate</li><li>• Built-in IR LED, max IR distance: 80 m</li><li>• ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments</li><li>• Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes</li><li>• <b>Intelligent detection:</b> Intrusion, tripwire</li><li>• <b>Abnormality detection:</b> Motion detection, video tampering, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, local alarm, voltage detection, audio detection</li><li>• <b>Alarm:</b> 1 in, 1 out; audio: 1 in, 1 out; supports max. 256 GB Micro SD card</li><li>• 12V DC/POE power support supply</li><li>• IP67 protection, IK10 protection (optional)</li></ul>	58,800,000
24	 <b>DH-IPC-HDBW2831EP-S-S2</b>	<p>“8MP Lite IR Fixed-focal Dome Network Camera”</p> <ul style="list-style-type: none"><li>• 8MP, 1/2.7" CMOS image sensor, low illuminance, high image definition</li><li>• Outputs max. 8MP (3840 × 2160) @15 fps, and supports 2688×1520 (2688 × 1520) @25/30 fps</li><li>• H.265 codec, high compression rate, ultra-low bit rate</li><li>• Built-in IR LED, max IR distance: 30 m</li><li>• ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments</li><li>• Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes</li><li>• <b>Intelligent detection:</b> Intrusion, tripwire</li><li>• <b>Abnormality detection:</b> Motion detection, video tampering, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, voltage detection</li><li>• Supports max. 256 GB Micro SD card</li><li>• 12V DC/PoE power supply</li><li>• IP67, IK10 protection</li></ul>	55,650,000

NO.	Model   Appearance	Specification	Price (IRR)
25	 <b>DH-IPC-HFW2831SP-S-S2</b>	<p><b>"8MP Lite IR Fixed-focal Bullet Network Camera"</b></p> <ul style="list-style-type: none"> <li>• 8MP, 1/2.7" CMOS image sensor, low illuminance, high image definition</li> <li>• Outputs max. 8MP (3840 × 2160) @15 fps, and supports 2688×1520 (2688 × 1520) @25/30 fps</li> <li>• H.265 codec, high compression rate, ultra-low bit rate</li> <li>• Built-in IR LED, max IR distance: 30 m</li> <li>• ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments</li> <li>• Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes</li> <li>• <b>Intelligent detection:</b> Intrusion, tripwire · Abnormality detection: Motion detection, video tampering, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, voltage detection</li> <li>• Supports max. 256 GB Micro SD card</li> <li>• 12V DC/PoE power supply</li> <li>• IP67 protection</li> </ul>	54,600,000
26	 <b>DH-IPC-HDW2831TP-AS-S2</b> 	<p><b>"8MP Lite IR Fixed-focal Eyeball Network Camera"</b></p> <ul style="list-style-type: none"> <li>• 8MP, 1/2.7" CMOS image sensor, low illuminance, high image definition</li> <li>• Outputs max. 8MP (3840 × 2160) @15 fps, and supports 2688×1520 (2688 × 1520) @25/30 fps</li> <li>• H.265 codec, high compression rate, ultra-low bit rate</li> <li>• Built-in IR LED, max IR distance: 30 m</li> <li>• ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments</li> <li>• Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes</li> <li>• <b>Intelligent detection:</b> Intrusion, tripwire</li> <li>• <b>Abnormality detection:</b> Motion detection, video tampering, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, voltage detection</li> <li>• Supports max. 256 GB Micro SD card, built-in MIC</li> <li>• 12V DC/PoE power supply</li> <li>• IP67 protection</li> </ul>	54,600,000

NO.	Model   Appearance	Specification	Price (IRR)
27	 <b>DH-IPC-HFW1830SP-S6</b>	<p><b>"8MP Entry IR Fixed-focal Bullet Network Camera"</b></p> <ul style="list-style-type: none"> <li>• 8MP 1/2.7" CMOS image sensor, low luminance, and high definition image.</li> <li>• Outputs max. 8MP (3840 × 2160) @15 fps and supports 2688 × 1520 (2688 × 1520) @25/30 fps</li> <li>• H.265 codec, high compression rate, and ultra-low bit rate.</li> <li>• Built-in IR LED, and the max. illumination distance is 30 m.</li> <li>• ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments.</li> <li>• Rotation mode, DWDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes.</li> <li>• <b>Abnormality detection:</b> Motion detection, video tampering, audio detection, network disconnection, IP conflict, and illegal access.</li> <li>• 12 V DC/PoE power supply.</li> <li>• IP67 protection.</li> </ul>	47,500,000
28	 <b>DH-IPC-HDW2531TP-ZS-S2</b>	<p><b>"5MP Lite IR Vari-focal Eyeball Network Camera"</b></p> <ul style="list-style-type: none"> <li>• 5MP, 1/2.7" CMOS image sensor, low illuminance, high image definition</li> <li>• Outputs max. 5MP (2592 × 1944) @20 fps, and supports 2688 × 1520 (2688 × 1520) @25/30 fps</li> <li>• H.265 codec, high compression rate, ultra-low bit rate</li> <li>• Built-in IR LED, max IR distance: 40 m</li> <li>• ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments</li> <li>• Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes</li> <li>• <b>Intelligent detection:</b> Intrusion, tripwire</li> <li>• <b>Abnormality detection:</b> Motion detection, video tampering, no SD card, SD card full, SD card error, network disconnected, IP conflict, illegal access, voltage detection</li> <li>• Supports max. 256 GB Micro SD card</li> <li>• 12V DC/PoE power supply</li> <li>• IP67 protection</li> </ul>	54,000,000

NO.	Model   Appearance	Specification	Price (IRR)
29	 <b>DH-IPC-HFW2531TP-AS-S2</b> <span style="color: red;">●</span>	<p>“5MP Lite IR Fixed-focal Bullet Network Camera”</p> <ul style="list-style-type: none"> <li>• 5MP, 1/2.7" CMOS image sensor, low illuminance, high image definition</li> <li>• Outputs max. 5MP (2592 × 1944) @20 fps, and supports 2688 × 1520 (2688 × 1520) @25/30 fps</li> <li>• H.265 codec, high compression rate, ultra-low bit rate</li> <li>• Built-in IR LED, max IR distance: 80 m</li> <li>• ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments</li> <li>• Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes</li> <li>• Intelligent detection: Intrusion, tripwire</li> <li>• Abnormality detection: Motion detection, video tampering, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, local alarm, voltage detection, audio detection</li> <li>• Alarm: 1 in, 1 out; audio: 1 in, 1 out; supports max. 256 GB Micro SD card</li> <li>• 12V DC/POE power support supply</li> <li>• IP67 protection, IK10 protection (optional)</li> </ul>	49,500,000
30	 <b>DH-IPC-HFW2531SP-S-S2</b>	<p>“5MP Lite IR Fixed-focal Bullet Network Camera”</p> <ul style="list-style-type: none"> <li>• 5MP, 1/2.7" CMOS image sensor, low illuminance, high image definition</li> <li>• Outputs max. 5MP (2592 × 1944) @20 fps, and supports 2688 × 1520 (2688 × 1520) @25/30 fps</li> <li>• H.265 codec, high compression rate, ultra-low bit rate</li> <li>• Built-in IR LED, max IR distance: 30 m</li> <li>• ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments</li> <li>• Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes</li> <li>• Intelligent detection: Intrusion, tripwire</li> <li>• Abnormality detection: Motion detection, video tampering, no SD card, SD card full, SD card error, network disconnected, IP conflict, illegal access, voltage detection</li> <li>• Supports max. 256 GB Micro SD card</li> <li>• 12V DC/PoE power supply</li> <li>• IP67 protection</li> </ul>	33,000,000

NO.	Model   Appearance	Specification	Price (IRR)
31	 <b>DH-IPC-HDW2531TP-AS-S2</b> <span style="color: red;">()</span>	<p>“5MP Lite IR Fixed-focal Eyeball Network Camera”</p> <ul style="list-style-type: none"> <li>• 5MP, 1/2.7" CMOS image sensor, low illuminance, high image definition</li> <li>• Outputs max. 5MP (2592 × 1944) @20 fps, and supports 2688 × 1520 (2688 × 1520) @25/30 fps</li> <li>• H.265 codec, high compression rate, ultra-low bit rate</li> <li>• Built-in IR LED, max IR distance: 40 m</li> <li>• ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments</li> <li>• Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes</li> <li>• <b>Intelligent detection:</b> Intrusion, tripwire</li> <li>• <b>Abnormality detection:</b> Motion detection, video tampering, no SD card, SD card full, SD card error, network disconnected, IP conflict, illegal access, voltage detection</li> <li>• Supports max. 256 GB Micro SD card</li> <li>• 12V DC/PoE power supply</li> <li>• IP67 protection</li> </ul>	33,000,000
32	 <b>DH-IPC-HFW2431TP-ZAS-S2</b>	<p>“4MP Lite IR Vari-focal Bullet Network Camera”</p> <ul style="list-style-type: none"> <li>• 4MP, 1/3" CMOS image sensor, low illuminance, high image definition</li> <li>• Outputs 4MP (2560 × 1440) @25/30 fps, max. supports 4MP (2688 × 1520) @20 fps</li> <li>• H.265 codec, high compression rate, ultra-low bit rate</li> <li>• Built-in IR LED, max IR distance: 60 m</li> <li>• ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments</li> <li>• Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes</li> <li>• <b>Intelligent detection:</b> Intrusion, tripwire</li> <li>• <b>Abnormality detection:</b> Motion detection, video tampering, no SD card, SD card full, SD card error, network disconnected, IP conflict, illegal access, local alarm, voltage detection, audio abnormal</li> <li>• <b>Alarm:</b> 1 in, 1 out; audio: 1 in, 1 out; supports max. 256 GB Micro SD card</li> <li>• 12V DC/PoE power supply</li> <li>• IP67 protection, IK10 protection (optional)</li> <li>• 12V DC/PoE power supply</li> </ul>	48,500,000

NO.	Model   Appearance	Specification	Price (IRR)
33	 <b>DH-IPC-HFW2439SP-LED-S2</b> <div style="background-color: #ffccbc; padding: 2px 5px; display: inline-block;"> <span>Full-Color</span> </div>	<p><b>"4MP IR Fixed focal Eyeball WizSense Network Camera"</b></p> <ul style="list-style-type: none"> <li>• 4MP, 1/3" CMOS image sensor, low illuminance, high image definition</li> <li>• Outputs max. 4MP (2688 × 1520) @30 fps</li> <li>• H.265 codec, high compression rate, low bit rate</li> <li>• Built-in IR LED, max. IR distance: 30 m</li> <li>• ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments</li> <li>• Rotation mode, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes</li> <li>• <b>Intelligent detection:</b> Intrusion, tripwire (support the classification and accurate detection of vehicle and human)</li> <li>• <b>Abnormality detection:</b> Motion detection, video tampering, scene changing, audio detection, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, voltage detection</li> <li>• Supports max. 256 G Micro SD card</li> <li>• 12V DC/POE power supply</li> <li>• IP67 protection</li> <li>• SMD Plus</li> </ul> <p> <a href="#">DH-IPC-HFW2439SP-LED-S2 دوribin madarasteh tخت شبکه داهوا مدل</a></p>	33,000,000
34	 <b>DH-IPC-HFW2431SP-S-S2</b>	<p><b>"4MP Lite IR Fixed-focal Bullet Network Camera"</b></p> <ul style="list-style-type: none"> <li>• 4MP, 1/3" CMOS image sensor, low illuminance, high image definition</li> <li>• Outputs 4MP (2560 × 1440) @25/30fps, Max. supports 4MP (2688 × 1520) @20 fps</li> <li>• H.265 codec, high compression ration, ultra-low bit rate</li> <li>• Built-in IR LED, max IR distance: 30 m</li> <li>• ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments</li> <li>• Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes</li> <li>• <b>Intelligent detection:</b> Intrusion, tripwire</li> <li>• <b>Abnormality detection:</b> Motion detection, video tampering, no SD card, SD card full, SD card error, network disconnected, IP conflict, illegal access, voltage detection</li> <li>• Supports max. 256 GB Micro SD card</li> <li>• 12V DC/PoE power supply</li> <li>• IP67 protection</li> </ul> <p> <a href="#">DH-IPC-HFW2431SP-S-S2 دوribin madarasteh tخت شبکه داهوا مدل</a></p>	31,000,000

NO.	Model   Appearance	Specification	Price (IRR)
35	 <b>DH-IPC-HDW2439TP-AS-LED-S2</b> <span style="color: red;">MIC</span>	<p>“4MP IR Fixed focal Eyeball WizSense Network Camera”</p> <ul style="list-style-type: none"> <li>• 4MP, 1/3" CMOS image sensor, low illuminance, high image definition</li> <li>• Outputs 4MP (2560 × 1440) @ 25/30 fps, Max. supports 4MP</li> <li>• H.265 codec, high compression rate, ultra-low bit rate</li> <li>• Built-in warm lights, max. illumination distance: 30 m</li> <li>• ROI, SMART H.264+/H.265+, flexible coding, applicable to various</li> <li>• Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking,</li> <li>• <b>Intelligent detection:</b> Intrusion, tripwire</li> <li>• <b>Abnormality detection:</b> Motion detection, video tampering, scene</li> <li>• Supports max. 256 GB Micro SD card • Built-in Mic</li> <li>• 12V DC/PoE power supply</li> <li>• IP67 protection</li> </ul>	33,000,000
36	 <b>DH-IPC-HDW2431TP-AS-S2</b> <span style="color: red;">MIC</span>	<p>“4MP Lite IR Fixed-focal Eyeball Network Camera”</p> <ul style="list-style-type: none"> <li>• 4MP, 1/3" CMOS image sensor, low illuminance, high image definition</li> <li>• Outputs 4MP (2560 × 1440) @ 25/30 fps, Max. supports 4MP (2688 × 1520) @ 20 fps</li> <li>• H.265 coding, high compression ration, low bit rate</li> <li>• Built-in IR LED, max IR distance: 30 m</li> <li>• ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments</li> <li>• Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes</li> <li>• <b>Intelligent detection:</b> Intrusion, tripwire</li> <li>• <b>Abnormality detection:</b> Motion detection, video tampering, no SD card, SD card full, SD card error, network disconnected, IP conflict, illegal access, voltage detection</li> <li>• Max. 256 GB SD card • built-in Mic</li> <li>• 12V DC/POE power supply</li> <li>• IP67 protection</li> </ul>	31,000,000

NO.	Model   Appearance	Specification	Price (IRR)
37	 <b>DH-IPC-HDBW2431EP-S-S2</b>	<p>“4MP Lite IR Fixed-focal Dome Network Camera”</p> <ul style="list-style-type: none"> <li>• 4MP, 1/3" CMOS image sensor, low illuminance, high image definition</li> <li>• Outputs 4MP (2560 × 1440)@25/30fps, Max. supports 4MP (2688 × 1520)@20 fps</li> <li>• H.265 codec, high compression ration, ultra-low bit rate</li> <li>• Built-in IR LED, max IR distance: 30 m</li> <li>• ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments</li> <li>• Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes</li> <li>• <b>Intelligent detection:</b> Intrusion, tripwire</li> <li>• <b>Abnormality detection:</b> Motion detection, video tampering, no SD card, SD card full, SD card error, network disconnected, IP conflict, illegal access, voltage detection</li> <li>• Supports max. 256 GB Micro SD card</li> <li>• 12V DC/PoE power supply</li> <li>• IP67 protection</li> </ul>	31,000,000
38	 <b>DH-IPC-HFW1431SP</b>	<p>“4MP WDR IR Mini-Bullet Camera”</p> <ul style="list-style-type: none"> <li>• 1/3" 4Megapixel progressive CMOS</li> <li>• H.265 &amp; H.264 dual-stream encoding</li> <li>• 20fps@4M(2688×1520) &amp; 25/30fps@3M(2304×1296)</li> <li>• WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC</li> <li>• <b>Multiple network monitoring:</b> Web viewer, CMS(DSS/PSS) &amp; DMSS</li> <li>• 2.8 mm fixed lens (3.6 mm optional)</li> <li>• Max IR LEDs Length 30m</li> <li>• IP67, PoE</li> </ul>	29,000,000

 DH-IPC-HFW1431SP دوربین مداربسته تحت شبکه داهوا مدل

NO.	Model   Appearance	Specification	Price (IRR)
39	 <b>DH-IPC-HDW1431SP</b>	<p>“4MP WDR IR Eyeball Network Camera”</p> <ul style="list-style-type: none"> <li>• 1/3" 4Megapixel progressive CMOS</li> <li>• H.265 &amp; H.264 dual-stream encoding</li> <li>• 20fps@4M(2688×1520) &amp; 25/30fps@3M(2304×1296)</li> <li>• WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC</li> <li>• Multiple network monitoring: Web viewer, CMS(DSS/PSS) &amp; DMSS</li> <li>• 2.8 mm fixed lens (3.6 mm optional)</li> <li>• Max IR LEDs Length 30m</li> <li>• IP67, PoE</li> </ul>	23,000,000
40	 <b>DH-IPC-HFW1431S1P-S4</b>	<p>“4MP Entry IR Fixed-focal Bullet Netwok Camera”</p> <ul style="list-style-type: none"> <li>• 4MP, 1/3" CMOS image sensor, low illuminance, high image definition</li> <li>• Outputs 4MP (2560 × 1440) @25/30 fps, and supports max. 4MP (2688 × 1520) @20 fps</li> <li>• H.265 codec, high compression rate, ultra-low bit rate</li> <li>• Built-in IR LED, max. IR distance: 30 m</li> <li>• ROI, SMART H.264/H.265, flexible coding, applicable to various bandwidth and storage environments</li> <li>• Image Rotation, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes</li> <li>• Abnormality detection: Motion detection, video tampering, network disconnection, IP conflict, illegal access, voltage detection</li> <li>• 12V DC/PoE power support</li> <li>• IP67, protection</li> </ul>	24,500,000

 دوربین مداربسته تحت شبکه داهوا مدل DH-IPC-HFW1431S1P-S4

NO.	Model   Appearance	Specification	Price (IRR)
41	 <b>DH-IPC-HDW1431T1P</b>	<p>“4MP Entry IR Fixed-focal Eyeball Network Camera”</p> <ul style="list-style-type: none"> <li>• 4MP Entry IR Fixed-focal Eyeball Network Camera</li> <li>• 1/3"4Megapixel progressive CMOS 20fps@4.1M(2688×1520) &amp; 25fps@4M(2560×1440)</li> <li>• H.265+/H.265/H.264+/H.264 dual-stream encoding WDR(120dB)</li> <li>• Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC Support ROI</li> <li>• Max. IR LEDs Length 30m</li> <li>• IP67, PoE</li> </ul>	25,500,000
42	 <b>DH-IPC-HFW2239SP-SA-LED</b> <span>Full-Color</span>	<p>“2MP Lite Full-color Fixed-focal Bullet Network Camera”</p> <ul style="list-style-type: none"> <li>• 2MP, 1/2.8" CMOS image sensor, low illuminance, high image definition</li> <li>• Outputs max. 2MP (1920 × 1080) @25/30 fps</li> <li>• H.265 codec, high compression rate, ultra-low bit rate</li> <li>• Built-in warm lights, max. illumination distance: 30 m</li> <li>• ROI, SMART H.264+/H.265+, flexible coding, applicable to various</li> <li>• Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking,</li> <li>• <b>Intelligent detection:</b> Intrusion, tripwire</li> <li>• <b>Abnormality detection:</b> Motion detection, video tampering, scene</li> <li>• Supports max. 256 GB Micro SD card • built-in Mic</li> <li>• 12V DC/PoE power supply</li> <li>• IP67 protection</li> </ul>	30,600,000

 دو ری بن مداربسته تحت شبکه داهوا مدل DH-IPC-HFW2239SP-SA-LED

NO.	Model   Appearance	Specification	Price (IRR)
43	 <b>DH-IPC-HDW2239TP-AS-LED</b> <span style="color: red;">●</span>	<p>“2MP Lite Full-color Fixed-focal Eyeball Network Camera”</p> <ul style="list-style-type: none"> <li>• 2MP, 1/2.8" CMOS image sensor, low illuminance, high image definition</li> <li>• Outputs max. 2MP (1920 × 1080) @25/30 fps</li> <li>• H.265 codec, high compression rate, ultra-low bit rate</li> <li>• Built-in warm lights, max. illumination distance: 30 m</li> <li>• ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments</li> <li>• Rotation mode, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes</li> <li>• <b>Intelligent detection:</b> Intrusion, tripwire</li> <li>• <b>Abnormality detection:</b> Motion detection, video tampering, scene changing, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, voltage detection</li> <li>• Built-in Mic</li> <li>• Supports max. 256 GB Micro SD card</li> <li>• 12V DC/PoE power supply</li> </ul> <span style="color: blue;">☰</span> <a href="#">دوربین مداربسته تحت شبکه داهوا مدل DH-IPC-HDW2239TP-AS-LED</a>	30,600,000
44	 <b>DH-IPC-HFW2231SP-S-S2</b>	<p>“2MP Lite IR Fixed-focal Bullet Network Camera”</p> <ul style="list-style-type: none"> <li>• 2MP, 1/2.8" CMOS image sensor, low illuminance, high image definition</li> <li>• Outputs max. 2MP (1920 × 1080) @25/30 fps</li> <li>• H.265 codec, high compression rate, ultra-low bit rate</li> <li>• Built-in IR LED, max. IR distance: 30 m</li> <li>• ROI, SMART H.264/H.265, flexible coding, applicable to various bandwidth and storage environments</li> <li>• Rotation mode, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes</li> <li>• <b>Intelligent detection:</b> Intrusion, tripwire</li> <li>• <b>Abnormality detection:</b> Motion detection, video tampering, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, voltage detection</li> <li>• Supports max. 256 GB Micro SD card</li> <li>• 12V DC/PoE power support</li> <li>• IP67 protection</li> </ul> <span style="color: blue;">☰</span> <a href="#">دوربین مداربسته تحت شبکه داهوا مدل DH-IPC-HFW2231SP-S-S2</a>	29,500,000

NO.	Model   Appearance	Specification	Price (IRR)
45	 <b>DH-IPC-HDBW2231EP-S-S2</b>	<p>“2MP Lite IR Fixed-focal Dome Network Camera”</p> <ul style="list-style-type: none"> <li>• 2MP, 1/2.8" CMOS image sensor, low illuminance, high image definition</li> <li>• Outputs 2MP (1920 × 1080) @ 25/30 fps</li> <li>• H.265 codec, high compression rate, ultra-low bit rate</li> <li>• Built-in IR LED, max IR distance: 30 m</li> <li>• ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments</li> <li>• Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes</li> <li>• <b>Intelligent detection:</b> Intrusion, tripwire</li> <li>• <b>Abnormality detection:</b> Motion detection, video tampering, no SD card, SD card full, SD card error, network disconnected, IP conflict, illegal access, voltage detection</li> <li>• Supports max. 256 GB Micro SD card</li> <li>• 12V DC/PoE power supply</li> <li>• IP67, IK10 protection</li> </ul>	29,700,000
46	 <b>DH-IPC-HFW2230SP-S-S2</b>	<p>“2MP Lite IR Fixed-focal Bullet Network Camera”</p> <ul style="list-style-type: none"> <li>• 2MP, 1/2.7" CMOS image sensor, low illuminance, high image definition</li> <li>• Outputs 2MP (1920 × 1080) @ 25/30 fps</li> <li>• H.265 codec, high compression rate, ultra-low bit rate</li> <li>• Built-in IR LED, max IR distance: 30 m</li> <li>• ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments</li> <li>• Rotation mode, DWDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes</li> <li>• <b>Intelligent detection:</b> Intrusion, tripwire</li> <li>• <b>Abnormality detection:</b> Motion detection, video tampering, no SD card, SD card full, SD card error, network disconnected, IP conflict, illegal access, voltage detection</li> <li>• Supports max. 256 GB Micro SD card</li> <li>• 12V DC/POE power supply</li> <li>• IP67 protection</li> </ul>	26,500,000

NO.	Model   Appearance	Specification	Price (IRR)
47	 <b>DH-IPC-HDBW2230EP-S-S2</b>	<p>“2MP Lite IR Fixed-focal Dome Network Camera”</p> <ul style="list-style-type: none"> <li>• 2MP, 1/2.7" CMOS image sensor, low illuminance, high image definition</li> <li>• Outputs 2MP (1920 × 1080)@25/30 fps</li> <li>• H.265 codec, high compression rate, ultra-low bit rate</li> <li>• Built-in IR LED, max IR distance: 30m</li> <li>• ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments</li> <li>• Rotation mode, DWDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes</li> <li>• <b>Intelligent detection:</b> Intrusion, tripwire</li> <li>• <b>Abnormality detection:</b> Motion detection, video tampering, no SD card, SD card full, SD card error, network disconnected, IP conflict, illegal access, voltage detection</li> <li>• Supports max. 256 GB Micro SD card</li> <li>• 12V DC/PoE power supply</li> <li>• IP67, IK10 protection</li> </ul> <p> <a href="#">DH-IPC-HDBW2230EP-S-S2 دویرین مداربسته تحت شبکه داهوا مدل</a></p>	26,900,000
48	 <b>DH-IPC-HDBW1230EP-S2</b>	<p>“2MP IR Mini-Dome Network Camera”</p> <ul style="list-style-type: none"> <li>• 1/2.7" 2Megapixel progressive CMOS</li> <li>• H.265 &amp; H.264 dual-stream encoding</li> <li>• 25/30fps@1080P(1920x1080)</li> <li>• DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC</li> <li>• Multiple network monitoring: Web viewer, CMS(DSS/PSS) &amp; DMSS</li> <li>• 2.8mm fixed lens (3.6mm optional)</li> <li>• Max IR LEDs length 30m</li> <li>• IP 67, IK10, PoE</li> </ul> <p> <a href="#">DH-IPC-HDBW1230EP-S2 دویرین مداربسته تحت شبکه داهوا مدل</a></p>	21,900,000

NO.	Model   Appearance	Specification	Price (IRR)
49	 <b>DH-IPC-HFW1230SP</b>	<p><b>"2MP IR Mini-Bullet Network Camera"</b></p> <ul style="list-style-type: none"> <li>• 1/2.7" 2Megapixel progressive CMOS</li> <li>• Smart H.265&amp; H.264 dual-stream encoding</li> <li>• 25/30fps@1080P(1920×1080)</li> <li>• DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC</li> <li>• <b>Multiple network monitoring:</b> Web viewer, CMS(DSS/PSS) &amp; DMSS</li> <li>• 2.8 mm fixed lens (3.6mm optional)</li> <li>• Max IR LEDs Length 30m</li> <li>• IP67, PoE</li> </ul>	21,900,000
50	 <b>DH-IPC-HFW1239S1P-LED</b>	<p><b>Full-Color</b></p> <p><b>"2MP Lite Full-color Fixed-focal Bullet Netwok Camera"</b></p> <ul style="list-style-type: none"> <li>• 2MP, 1/2.7" CMOS image sensor, low illuminance, high image definition</li> <li>• Outputs max. 2MP(1920 × 1080)@25/30 fps</li> <li>• H.265 codec, high compression rate, ultra-low bit rate</li> <li>• Built-in LEDs, max LED distance: 15 m</li> <li>• ROI, SMART H.264/H.265, flexible coding, applicable to various bandwidth and storage environments</li> <li>• Rotation mode, DWDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes</li> <li>• <b>Abnormality detection:</b> Motion detection, video tampering, network disconnection, IP conflict, illegal access</li> <li>• 12V DC/PoE power support,IP67 protection</li> </ul>	21,300,000

 دوربین مداربسته تحت شبکه داهوا مدل DH-IPC-HFW1239S1P-LED

NO.	Model   Appearance	Specification	Price (IRR)
51	 <b>DH-IPC-HDW1239T1P-LED</b> <span style="background-color: yellow; border: 1px solid black; padding: 2px;">Full-Color</span>	<p>“2MP Lite Full-color Fixed-focal Eyeball Network Camera”</p> <ul style="list-style-type: none"> <li>• 2MP, 1/2.7" CMOS image sensor, low illuminance, high image definition</li> <li>• Outputs max. 2MP (1920 × 1080) @25/30 fps</li> <li>• H.265 codec, high compression rate, ultra-low bit rate</li> <li>• Built-in LEDs, max LED distance: 15 m</li> <li>• ROI, SMART H.264/H.265, flexible coding, applicable to various bandwidth and storage environments</li> <li>• Rotation mode, DWDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes</li> <li>• <b>Abnormality detection:</b> Motion detection, video tampering, network disconnection, IP conflict, illegal access</li> <li>• 12V DC/PoE power support, IP67 protection</li> </ul>	21,300,000
52	 <b>DH-IPC-HFW1230S1P</b>	<p>“2MP Entry IR Fixed-Focal Bullet Network Camera”</p> <ul style="list-style-type: none"> <li>• 2MP, 1/2.7" CMOS image sensor, low illuminance, high image definition</li> <li>• Outputs max. 2MP (1920 × 1080) @25/30 fps</li> <li>• H.265 codec, high compression rate, ultra-low bit rate</li> <li>• Built-in IR LED, max. IR distance: 15 m</li> <li>• ROI, SMART H.264/H.265, flexible coding, applicable to various bandwidth and storage environments</li> <li>• Rotation mode, DWDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes</li> <li>• 12V DC/PoE power support</li> <li>• IP67 protection</li> </ul>	19,000,000

 DH-IPC-HFW1230S1P دوربین مداربسته تحت شبکه داهوا مدل

NO.	Model   Appearance	Specification	Price (IRR)
53	 <b>DH-IPC-HDW1230T1P</b>	<p>“2MP Entry IR Fixed-Focal Eyeball Netwok Camera</p> <ul style="list-style-type: none"> <li>• 1/2.7” 2Megapixel progressive CMOS</li> <li>• H.265 &amp; H.264 dual-stream encoding</li> <li>• 25/30fps@1080P(1920x1080)</li> <li>• DWDR, Day/Night(ICR), 3DNR, HLC, AGC, BLC, ROI-EIS</li> <li>• <b>Multiple network monitoring:</b> Web viewer, CMS(DSS/PSS) &amp; DMSS</li> <li>• 2.8 mm fixed lens (3.6mm optional)</li> <li>• Max IR LEDs Length 30m</li> <li>• IP67, PoE</li> </ul>	19,000,000
54	 <b>DH-IPC-HDW1230SP</b>	<p>“2MP IR Eyeball Network Camera”</p> <ul style="list-style-type: none"> <li>• 1/2.7” 2Megapixel progressive CMOS</li> <li>• H.265 &amp; H.264 dual-stream encoding</li> <li>• 25/30fps@1080P(1920x1080)</li> <li>• DWDR, Day/Night(ICR), 3DNR, HLC, AGC, BLC</li> <li>• <b>Multiple network monitoring:</b> Web viewer, CMS(DSS/PSS) &amp; DMSS</li> <li>• 2.8 mm fixed lens (3.6mm optional)</li> <li>• Max IR LEDs Length 30m</li> <li>• IP67, PoE</li> </ul>	20,900,000

 DH-IPC-HDW1230SP دوربین مداربسته تحت شبکه داهوا مدل

## PTZ Camera

NO.	Model   Appearance	Specification	Price (IRR)
55	<b>DH-SD6CE445XA-HNR</b> <i>Wiz Sense</i> 	<p>“4MP 45x Starlight IR WizSense Network PTZ Camera”</p> <ul style="list-style-type: none"> <li>• 1/2.8" 4Megapixel STARVIST™ Progressive CMOS</li> <li>• H.265+/H.265/H.264+/H.264/MJPEG(Sub Stream) Max. 25/30fps@4MP</li> <li>• Minimum Illumination Color: 0.005 Lux@F1.6; B/W: 0.0005 Lux@F1.6; 0 Lux@F1.6 (IR on)</li> <li>• 3.95 mm-177.75 mm Powerful 45x optical zoom Max. Aperture F1.6-F4.95</li> <li>• Pan/Tilt Range Pan: 0°-360° endless; Tilt: -20°-90°,auto flip 180° Preset Speed Pan: 300° /s; Tilt: 200° /s</li> <li>• WDR 120db, BLC, HLC, Auto ICR, AWB, AGC, 2D/3D DNR, ROI, EIS, Defog</li> <li>• Deep-learning-based auto tracking and perimeter protection</li> <li>• Face detection, SMD Plus, Tripwire, Intrusion. Human/Vehicle/Motor-non Motor Vehicle Detection</li> <li>• Up to 300 presets, 8 tour, 5 pattern, Auto scan, Auto Pan</li> <li>• Micro SD card (256G), 1/1 Audio I/O, 7/2 Alarm I/O, ONVIF Profile S&amp;G&amp;T</li> <li>• IR distance up to 250m, DC 24 V/2.5 A, PoE+, IP67, IK10</li> </ul>	446,250,000
56	<b>DH-SD5A445XA-HNR</b> <i>Wiz Sense</i> 	<p>“4MP 45x Starlight IR WizSense Network PTZ Camera”</p> <ul style="list-style-type: none"> <li>• 1/2.8" 4Megapixel STARVIST™ Progressive CMOS</li> <li>• H.265/H.265+/H.264+/H.264/MJPEG(Sub Stream) 3 Streams, Max. 25/30fps@4M</li> <li>• Min. Illumination Color: 0.005 Lux@F1.6 B/W: 0.0005 Lux@F1.6 0Lux (IR light on)</li> <li>• 3.95 mm-177.7 mm Powerful 45x optical zoom Max. Aperture F1.6-F4.95</li> <li>• Max Presets Speed: Pan: 400°/s Tilt: 300°/s, Pan: 0°-360° endless rotation</li> <li>• WDR(120), EIS, Defog, ROI, 2D DNR, 3D DNR, HLC, BLC, AWB, AGC, Day/Night Auto ICR</li> <li>• Deep Learning, Auto Track, Tripwire, intrusion, Object Abandoned/Missing, SMD Plus, Face Detection, human/motor vehicle/non-motor vehicle Classification, Animals/Leaves/Light False Alarm Filtering</li> <li>• Up to 300 presets, 8 tour, 5 pattern, Auto scan, Auto Pan</li> <li>• Micro SD card (256G), 1/1 Audio I/O, 2/1 Alarm I/O, ONVIF Profile S&amp;G&amp;T</li> <li>• IR distance up to 150m, DC 24 V/2.5 A, PoE+, IP67, IK10, 6000V lightning proof; surge protection</li> </ul>	414,000,000

NO.	Model   Appearance	Specification	Price (IRR)
57	<b>DH-SD49225XB-HNR</b> <i>Wiz Sense</i> 	<p>“2MP 25x Starlight IR WizSense Network PTZ Camera</p> <ul style="list-style-type: none"> <li>• 4MP 25x Starlight IR WizSense Network PTZ Camera</li> <li>• 1/2.8" STARVIS™ Progressive CMOS</li> <li>• H.265+/H.265/H.264+/H.264/MJPEG (sub stream)</li> <li>• Max.25/30fps@4M, 960P, 720P</li> <li>• 4.8mm~120mm 25x optical zoom</li> <li>• Max 240°/s pan speed, 360° endless pan rotation</li> <li>• WDR(120dB), Day/Night(ICR)(Color/B/W), Ultra DNR(2D/3D), BLC, HLC, AWB, AGC, Auto iris, Auto focus</li> <li>• IVS(Tripwire, Intrusion, Abandoned/Missing, Face Detection, Human, Vehicle, SMD Plus, Region of Interest)</li> <li>• False Alarm Avoidance for Animals, Leaves, Bright Light</li> <li>• Support Defog and EIS</li> <li>• Up to 300 presets, 8 tour, 5 pattern, Auto scan, Auto Pan</li> <li>• Built-in 2/1 Alarm in/out, Audio 1/1 in/out, Support PoE+</li> </ul>	195,000,000
58	<b>DH-SD5A232XB-HNR</b> <i>Wiz Sense</i> 	<p>“2MP 32x Starlight IR WizSense Network PTZ Camera”</p> <ul style="list-style-type: none"> <li>• 1/2.8" 2Megapixel STARVIS™ CMOS</li> <li>• 32x optical zoom, Max. 50/60fps@2M</li> <li>• Min Illumination Color: 0.005 lux@F1.6, Focal Length 4.8 mm~154 mm</li> <li>• Smart H.265+; H.265; Smart H.264+; H.264B</li> <li>• Face detection, tracking and perimeter protection, SMD PLUS</li> <li>• IR distance up to 150 m, PoE+, IP67, IK10</li> <li>• WDR(120db), Day/Night(ICR), 3DNR, AWB, AGC, BLC</li> </ul>	325,500,000

NO.	Model   Appearance	Specification	Price (IRR)
59	 <b>DH-SD59230U-HNI</b>	<p>“2MP 30x Starlight IR PTZ Network Camera”</p> <ul style="list-style-type: none"> <li>• H.265+/H.265/H.264+/H.264 Encoding</li> <li>• Max. 50/60fps@1080P, 25/30/50/60fps@720P 4.5mm~135mm 30x optical zoom</li> <li>• Max 400°/s pan speed, 360° endless pan rotation</li> <li>• WDR(120dB), Day/Night(ICR), Ultra DNR, Auto iris, Auto focus</li> <li>• Auto-tracking and IVS(Tripwire, Intrusion, Abandoned/Missing, Face Detection), Support Defog and EIS Up to 300</li> <li>• presets, 8 tour, 5 pattern, Auto scan, Auto Pan</li> <li>• Built-in 2/1 Alarm in/out, Audio 1/1 in/out</li> <li>• Support PoE+, IR Distance up to 150m</li> <li>• IP66, OSD</li> </ul>	250,000,000
60	 <b>DH-SD59225U-HNI</b>	<p>“2MP 25x Starlight IR PTZ Network Camera 1/2.8" Exmor R CMOS ”</p> <ul style="list-style-type: none"> <li>• H.265+/H.265/H.264+/H.264 Encoding</li> <li>• Max. 50/60fps@1080P, 25/30/50/60fps@720P 4.8mm~120mm 25x optical zoom</li> <li>• Max 400°/s pan speed, 360° endless pan rotation</li> <li>• WDR(120dB), Day/Night(ICR), Ultra DNR, Auto iris, Auto focus</li> <li>• Auto-tracking and IVS(Tripwire, Intrusion, Abandoned/Missing, Face Detection), Support Defog and EIS Up to 300</li> <li>• presets, 8 tour, 5 pattern, Auto scan, Auto Pan</li> <li>• Built-in 2/1 Alarm in/out, Audio 1/1 in/out</li> <li>• Support PoE+, IR Distance up to 150m,</li> <li>• IP66, OSD</li> </ul>	166,000,000



دوربین مداربسته تحت شبکه داهوا مدل DH-SD59230U-HNI



دوربین مداربسته تحت شبکه داهوا مدل DH-SD59225U-HNI

NO.	Model   Appearance	Specification	Price (IRR)
61	 <b>DH-SD49225XA-HNR</b>	<p>“2MP 25x Starlight IR WizSense Network PTZ Camera”</p> <ul style="list-style-type: none"> <li>• 2MP 25x Starlight IR PTZ AI Network Camera</li> <li>• 1/2.8" STARVIS™ CMOS</li> <li>• H.265+/H.265/H.264+/H.264/MJPEG (sub stream)</li> <li>• Max. 1~60fps@1080P,960P,720P</li> <li>• 4.8mm~120mm 25x optical zoom</li> <li>• Max 240°/s pan speed, 360° endless pan rotation</li> <li>• WDR(120dB), Day/Night(ICR)(Color/B/W), Ultra DNR(2D/3D), BLC, HLC, AWB, AGC, Auto iris, Auto focus</li> <li>• IVS(Tripwire, Intrusion, Abandoned/Missing, Face Detection, Human, Vehicle, SMD Plus, Region of Interest)</li> <li>• False Alarm Avoidance for Animals, Leaves, Bright Light</li> <li>• Support Defog and EIS</li> <li>• Up to 300 presets, 8 tour, 5 pattern, Auto scan, Auto Pan</li> <li>• Built-in 2/1 Alarm in/out, Audio 1/1 in/out, Support PoE+</li> </ul> <p> DH-SD49225XA-HNR  دوربین مداربسته تحت شبکه داهوا مدل DH-SD49225XA-HNR</p>	160,000,000
62	 <b>DH-SD3A205-GNP-PV</b> <b>Wiz Sense</b>	<p>“2MP Starlight IR AI WizSense Network PTZ Camera”</p> <ul style="list-style-type: none"> <li>• H.265; H.264B; H.264M; H.264H; MJPEG; MJPEG (Sub Stream); H.265+; H.264+</li> <li>• Focal Length 2.7 mm~13.5 mm, Optical Zoom 5x</li> <li>• Tripwire and intrusion, Deep-learning-based perimeter protectionm SMD Plus</li> <li>• IR distance up to 30m</li> <li>• Starlight technology</li> <li>• Up to 300 presets</li> <li>• DWDR, HLC, BLC, AGC, AWB, 2D/3D DNR, Day/Night Auto (ICR), ROI, Defog</li> <li>• Built-in Mic, Built-in Speaker, Two Way Audio</li> <li>• ONVIF Profile S&amp;G&amp;T; CGI</li> <li>• IP66; TVS 2000V lightning proof; surge protection; voltage transient protection</li> </ul> <p> SD3A205-GNP-PV  دوربین مداربسته تحت شبکه داهوا مدل SD3A205-GNP-PV</p>	75,600,000

NO.	Model   Appearance	Specification	Price (IRR)
63	 <b>DH-SD29204T-GN</b>	<p>“ 2MP 4x IR PTZ Network Camera”</p> <ul style="list-style-type: none"> <li>• 1/2.7" 2MP CMOS Sensor, 2.7mm ~ 11mm, 4x Optical Zoom</li> <li>• H.264+/H.264 Encoding</li> <li>• Max. 25/30fps@1080P, 25/30/50/60fps@720P</li> <li>• WDR, Day/Night(ICR), Ultra DNR, Auto iris, Auto focus</li> <li>• Max 100°/s pan speed, 360° endless pan rotation</li> <li>• Up to 300 presets, 5 auto scan, 8 tour, 5 pattern</li> <li>• Built-in Mic, IR Distance up to 30m, POE, (Tripwire Intrusion   Scene Change   Face  Abandoned-Missing Object)</li> </ul>	65,000,000
64	 <b>DH-SD6CE245U-HNI</b>	<p>“2MP 45x Starlight IR PTZ Network Camera”</p> <ul style="list-style-type: none"> <li>• 1/2.8" 2Megapixel STARVIS™ CMOS</li> <li>• H.265+/H.265/H.264+/H.264 Triple-streams encoding</li> <li>• Minimum Illumination:Color(0.005Lux@F1.6), B/W(0.0005Lux@F1.6)</li> <li>• Max. 50/60fps@1080P, 3.95mm~177.7mm Focal Length</li> <li>• 45x optical zoom</li> <li>• WDR(120dB), Day/Night(ICR), Ultra DNR, BLC, HLC, AGC, AWB</li> <li>• Auto-tracking and IVS(Tripwire, Intrusion,Abandoned/Missing, Face Detection, Heat Map)</li> <li>• Support Defog, ROI, EIS</li> <li>• Up to 300 presets, 8 tour, 5 pattern, Auto scan, Auto Pan</li> <li>• 1*Video output, Rs485</li> <li>• 7/2 Alarm in/out, 1/1 Audio in/out</li> <li>• IR Distance up to 250m, PoE+, IP67, IK10</li> </ul>	<a href="#">Call</a>

 DH-SD29204T-GN دوربین مداربسته تحت شبکه داهوا مدل

NO.	Model   Appearance	Specification	Price (IRR)
65	 <b>DH-SD6C3425XB-HNR-A-PV1</b> <i>Wiz Sense</i>	<p>“4MP 25x Starlight IR WizSense Network PTZ Camera”</p> <ul style="list-style-type: none"> <li>• 1/2.8" 4Megapixel STARVIST™CMOS</li> <li>• Smart H.265+; H.265;Smart H.264+; H.264B;H.264H; MJPEG(Sub Stream) 3 Streams,Max.25/30fps@4M</li> <li>• Min. Illumination Color: 0.005 lux@F1.6,B/W: 0.0005 lux@F1.6,0 lux (IR light on)</li> <li>• 4.8 mm–120 mm Powerful 25x optical zoom Max.Aperture F1.6–F3.5</li> <li>• Max Preset Speed Pan: 240°/s; Tilt: 150°/s,Pan: 0° to 360° endless</li> <li>• Tilt: -20° to +90°, auto flip 180,Pan: 0.1°–160°/s; Tilt: 0.1°–60°/s" Manual Control Speed.</li> <li>• Up to 300 presets, 8 tour (up to 32 presets per tour), 5 pattern , 5 scan , Power-off Memory Support</li> <li>• Tripwire; intrusion; climbing fences; loitering detection; abandoned/missing object; fast moving; parking detection; people gathering; vehicle/human alarm classification; linkage tracking</li> <li>• Motor vehicle, non-motor vehicle, face, human body detection; optimization; capturing pictures; uploading high-quality face snapshots, SMD , Face Detection , Auto Tracking Support</li> <li>• Auto (ICR); Color; B/W, BLC, WDR, HLC, W/B, Elctronic defog, 16X digital Zoom</li> <li>• IR distance up to 150m, 24 VDC/2.5 A ± 25% (included), PoE+ (802.3at)</li> <li>• IP66, TVS 6000V lightning proof; surge protection; voltage transient protection</li> </ul> <p> DH-SD6C3425XB-HNR-A-PV1 دویرین مداربسته تحت شبکه داهوا مدل</p>	CALL
66	 <b>DHI-NVR1104HS-S3/H</b>	<p>“4 CH Compact 1U Lite H.265 Network Video Recorder”</p> <ul style="list-style-type: none"> <li>• New 4.0 user interface</li> <li>• P2P remote surveillance, video play on mobile device</li> <li>• <b>Max. decoding capability:</b> 1ch@8MP(30FPS) or 1ch@5MP(30FPS) or 2ch@4MP(30FPS) or 2ch@3MP(30FPS) or 4ch@1080P(30FPS)</li> <li>• Smart H.265+/Smart H.264+/H.265/H.264</li> <li>• 1 VGA/1 HDMI simultaneous video output, maximum resolution 1080P1 SATA 2.0 port Up to 8TB</li> <li>• 1 front USB 2.0 port, 1 rear USB 2.0 port, 1ch Audio I/O for Two Way Talk Only 1 RJ-45 port (10/100 Mbps)</li> <li>• Network Bandwidth 80 Mbps for access, 80 Mbps for storage and 60Mbps for forwarding. Up to 8MP Resolution for Preview &amp; Playback</li> <li>• ONVIF(profile T/profile S/profile G)</li> </ul> <p> Dستگاه ضبط تصویر تحت شبکه داهوا مدل</p>	22,800,000

NO.	Model   Appearance	Price (IRR)
67	<p><b>DHI-NVR2104HS-I</b> <i>Wiz Sense</i></p>  <p><b>4K AI</b></p> <p>"4 CH Compact 1U WizSense Network Video Recorder"</p> <ul style="list-style-type: none"> <li>• New 4.0 user interface • 4channel IP video access</li> <li>• Smart H.265+/Smart H.264+/H.265/H.264/MJPEG; H.265 auto switch</li> <li>• Up to 12MP resolution for live view and playback</li> <li>• AI disabled: 1-channel 12MP@30 fps; 1-channel 8MP@30 fps; 2-channel 5MP@30 fps; 3-channel 4MP@30 fps; 6-channel 1080p@30 fps</li> <li>• AI enabled: 1-channel 8MP@30 fps; 1-channel 5MP@30 fps; 2-channel 4MP@30 fps; 4-channel 1080p@30 fps</li> <li>• 80 Mbps for access, 80 Mbps for storage and 60 Mbps for forwarding</li> <li>• 2 channels Perimeter Protection by Camera, Search for pictures by channel, time and event type</li> <li>• 4 channels SMD Plus by Camera, Search by target classification (human, vehicle)</li> <li>• 1-channel face detection and recognition (AI by NVR); or 2-channel perimeter detection (AI by NVR); or 4-channel SMD (AI by NVR); up to 10 face databases and 5,000 face images</li> <li>• 1*HDMI, 1*VGA External Port, 1 front USB 2.0 port, 1 rear USB 2.0 port</li> <li>• 1 channel RCA connector Audio Input, 2 channels RCA connector, which supports voice intercom output</li> <li>• 1 SATA III ports, up to 8 TB for a single HDD</li> <li>• ONVIF(profile T/S/G); CGI; SDK Network Interoperability</li> <li>• Security baseline 2.1</li> </ul> <p> دستگاه ضبط تصویر تحت شبکه داهوا مدل ای</p>	50,400,000
68	<p><b>DHI-NVR2108HS-I</b> <i>Wiz Sense</i></p>  <p><b>4K AI</b></p> <p>"8 CH Compact 1U WizSense Network Video Recorder"</p> <ul style="list-style-type: none"> <li>• New 4.0 user interface • 8channel IP video access</li> <li>• Smart H.265+/Smart H.264+/H.265/H.264/MJPEG; H.265 auto switch</li> <li>• Up to 12MP resolution for live view and playback</li> <li>• AI disabled: 1-channel 12MP@30 fps; 1-channel 8MP@30 fps; 2-channel 5MP@30 fps; 3-channel 4MP@30 fps; 6-channel 1080p@30 fps</li> <li>• AI enabled: 1-channel 8MP@30 fps; 1-channel 5MP@30 fps; 2-channel 4MP@30 fps; 4-channel 1080p@30 fps</li> <li>• 80 Mbps for access, 80 Mbps for storage and 60 Mbps for forwarding</li> <li>• 2 channels Perimeter Protection by Camera, Search for pictures by channel, time and event type</li> <li>• 4 channels SMD Plus by Camera, Search by target classification (human, vehicle)</li> <li>• 1-channel face detection and recognition (AI by NVR); or 2-channel perimeter detection (AI by NVR); or 4-channel SMD (AI by NVR); up to 10 face databases and 5,000 face images</li> <li>• 1*HDMI, 1*VGA External Port, 1 front USB 2.0 port, 1 rear USB 2.0 port</li> <li>• 1 channel RCA connector Audio Input, 2 channels RCA connector, which supports voice intercom output</li> <li>• 1 SATA III ports, up to 8 TB for a single HDD</li> <li>• ONVIF(profile T/S/G); CGI; SDK Network Interoperability</li> <li>• Security baseline 2.1</li> </ul> <p> دستگاه ضبط تصویر تحت شبکه داهوا مدل ای</p>	44,500,000

NO.	Model   Appearance	Specification	Price (IRR)
69	<b>DH-NVR2108HS-I2</b> <i>Wiz Sense</i> <div style="display: flex; align-items: center;"> <span style="margin-right: 10px;">AI</span>  </div>	<p>“8 Channel Compact 1U 1HDD WizSense Network Video Recorder”</p> <ul style="list-style-type: none"> <li>New 4.0 user interface</li> <li>8channel IP video access</li> <li>Smart H.265+/Smart H.264+/H.265/H.264/MJPEG; H.265 auto switch</li> <li>Up to 12MP resolution for live view and playback</li> <li>AI disabled: 1-channel 12MP@30 fps; 1-channel 8MP@30 fps; 2-channel 5MP@30 fps; 3-channel 4MP@30 fps; 6-channel 1080p@30 fps</li> <li>AI enabled: 1-channel 8MP@30 fps; 1-channel 5MP@30 fps; 2-channel 4MP@30 fps; 4-channel 1080p@30 fps</li> <li>80 Mbps for access, 80 Mbps for storage and 60 Mbps for forwarding</li> <li>2 channels Perimeter Protection by Camera, Search for pictures by channel, time and event type</li> <li>4 channels SMD Plus by Camera, Search by target classification (human, vehicle)</li> <li>1-channel face detection and recognition (AI by NVR); or 2-channel perimeter detection (AI by NVR); or 4-channel SMD (AI by NVR); up to 10 face databases and 5,000 face images</li> <li>1*HDMI, 1*VGA External Port, 1 front USB 2.0 port, 1 rear USB 2.0 port</li> <li>1 channel RCA connector Audio Input, 2 channels RCA connector, which supports voice intercom output</li> <li>1 SATA III ports, up to 10 TB for a single HDD</li> <li>ONVIF(profile T/S/G); CGI; SDK Network Interoperability</li> <li>Security baseline 2.1</li> </ul> <div style="display: flex; align-items: center;"> <span style="margin-right: 10px;"></span> <a href="#">دستگاه ضبط تصویر تحت شبکه داهوا مدل DH-NVR2108HS-I2</a> </div>	43,500,000
70	<b>DH-NVR2108HS-4KS2</b> <div style="display: flex; align-items: center;">  </div>	<p>“8 Channel Compact 1U 8PoE Lite 4K H.265 Network Video Recorder”</p> <ul style="list-style-type: none"> <li>Max 80Mbps incoming bandwidth</li> <li>Up to 8Mp resolution preview&amp;playback</li> <li>Up to 1ch@8MP/4ch@1080P decoding</li> <li>HDMI/VGA simultaneous video output</li> <li>Support 1 SATA HDD up to10TB, 2 USB2.0</li> <li>80 Mbps Network Card, P2P support</li> </ul> <div style="display: flex; align-items: center;"> <span style="margin-right: 10px;"></span> <a href="#">دستگاه ضبط تصویر تحت شبکه داهوا مدل DH-NVR2108HS-4KS2</a> </div>	33,000,000

NO.	Model   Appearance	Specification	Price (IRR)
71	 <b>DHI-NVR2116HS-I</b> <i>Wiz Sense</i> <div style="display: flex; justify-content: space-around;"> <span>4K</span> <span>AI</span> </div>	<p>“16 CH Compact 1U WizSense Network Video Recorder”</p> <ul style="list-style-type: none"> <li>New 4.0 user interface</li> <li>• 16 channel IP video access</li> <li>• Smart H.265+/Smart H.264+/H.265/H.264/MJPEG; H.265 auto switch</li> <li>• Up to 12MP resolution for live view and playback</li> <li>• AI disabled: 1-channel 12MP@30 fps; 1-channel 8MP@30 fps; 2-channel 5MP@30 fps; 3-channel 4MP@30 fps; 6-channel 1080p@30 fps</li> <li>• AI enabled: 1-channel 8MP@30 fps; 1-channel 5MP@30 fps; 2-channel 4MP@30 fps; 4-channel 1080p@30 fps</li> <li>• 200 Mbps for access, 200 Mbps for storage and 100 Mbps for forwarding</li> <li>• 2 channels Perimeter Protection by Camera, Search for pictures by channel, time and event type</li> <li>• 4 channels SMD Plus by Camera, Search by target classification (human, vehicle)</li> <li>• 1 channel face detection and recognition (AI by NVR); or 2-channel perimeter detection (AI by NVR); or 4-channel SMD (AI by NVR); up to 10 face databases and 5,000 face images</li> <li>• 1*HDMI, 1*VGA External Port, 1 front USB 2.0 port, 1 rear USB 2.0 port</li> <li>• 1 channel RCA connector Audio Input, 2 channels RCA connector, which supports voice intercom output</li> <li>• 1 SATA III ports, up to 8 TB for a single HDD</li> <li>• ONVIF(profile T/S/G); CGI; SDK Network Interoperability</li> <li>• Security baseline 2.1</li> </ul> <p> DHI-NVR2116HS-I دستگاه ضبط تصویر تحت شبکه داهوا مدل ای</p>	56,100,000
72	 <b>DH-NVR2116HS-I2</b> <i>Wiz Sense</i> <div style="display: flex; justify-content: space-around;"> <span>4K</span> <span>AI</span> </div>	<p>“16 Channel Compact 1U 1HDD WizSense Network Video Recorder”</p> <ul style="list-style-type: none"> <li>Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format</li> <li>Network Bandwidth: AI off: Access: 144 Mbps; Storage: 144 Mbps; Forward: 72 Mbps</li> <li>AI on: Access: 72 Mbps; Storage: 72 Mbps; Forward: 36 Mbps</li> <li>Resolution: 12MP; 8MP; 5MP; 4MP; 3MP; 2MP; 720p; D1</li> <li>Decoding Capability: AI disabled: 1-channel 12MP@30 fps; 1-channel 8MP@30 fps; 2-channel 5MP@30 fps; 3-channel 4MP@30 fps; 6-channel 1080p@30 fps</li> <li>AI enabled: 1-channel 8MP@30 fps; 1-channel 5MP@30 fps; 2-channel 4MP@30 fps; 4-channel 1080p@30 fps</li> <li>1 × VGA, 1 × HDMI (simultaneous) 4K Output</li> <li>1-channel face detection and recognition (AI by NVR); 1-channel perimeter protection (AI by NVR); up to 10 face databases and 5,000 face images; 4-channel SMD Plus (AI by NVR);</li> <li>AI by camera: Face detection and recognition, perimeter protection, and SMD Plus</li> <li>1 SATA II port, up to 10TB</li> <li>1ch Audio I/O for Two Way Talk Only, 1 front USB 2.0 port, 1 rear USB 2.0 port</li> <li>1 RJ-45 port(1000Mbps), P2P Support, ONVIF(profile T/profile S/profile G)</li> </ul> <p> DH-NVR2116HS-I2 دستگاه ضبط تصویر تحت شبکه داهوا مدل ای</p>	54,600,000

NO.	Model   Appearance	Specification	Price (IRR)
73	 <b>DH-NVR2104HS-4KS2</b>	<p>“4 Channel Compact 1U Lite 4K H.265 Network Video Recorder”</p> <ul style="list-style-type: none"> <li>• H.265/H.264 codec decoding</li> <li>• Max 80Mbps incoming bandwidth</li> <li>• Up to 8Mp resolution preview&amp;playback</li> <li>• Up to 1ch@8MP/4ch@1080P decoding</li> <li>• HDMI/VGA simultaneous video output</li> <li>• Support 1 SATA HDD up to 6TB, 2 USB2.0</li> <li>• 100 Mbps Network Card, P2P support</li> </ul>	26,500,000
74	 <b>DH-NVR2108HS-4KS2</b>	<p>“8 Channel Compact 1U Lite 4K H.265 Network Video Recorder”</p> <ul style="list-style-type: none"> <li>• Max 80Mbps incoming bandwidth</li> <li>• Up to 8Mp resolution preview&amp;playback</li> <li>• Up to 1ch@8MP/4ch@1080P decoding</li> <li>• HDMI/VGA simultaneous video output</li> <li>• Support 1 SATA HDD up to 6TB, 2 USB2.0</li> <li>• 100 Mbps Network Card, P2P support</li> </ul>	32,000,000



دستگاه ضبط تصویر تحت شبکه داهوا مدل DH-NVR2104HS-4KS2



دستگاه ضبط تصویر تحت شبکه داهوا مدل DH-NVR2108HS-4KS2

NO.	Model   Appearance	Specification	Price (IRR)
75	 <b>DHI-NVR4108HS-4KS2/L</b> <span style="background-color: yellow; padding: 2px 5px;">4K</span>	<p><b>"8 CH Compact 1U 1HDD Network Video Recorder"</b></p> <ul style="list-style-type: none"> <li>New 4.0 user interface, Security baseline 2.1</li> <li>H.264, H.265, Smart H.264+, and Smart H.265+. H.265 auto switch</li> <li><b>Max. decoding capability:</b> 8 × 1080p@30 fps. Supports adaptive decoding</li> <li>Supports mainstream cameras of ONVIF and RTSP protocols</li> <li>P2P remote surveillance, video play on mobile device</li> <li>VGA/HDMI simultaneous video output, maximum resolution of HDMI is 4K</li> <li><b>AI by Camera:</b> Face detection, perimeter protection, IVS, people counting, heat map, and SMD</li> <li>Supports remote configuration and management of IPC, such as setting parameters, getting information, and upgrading IPC of the same model in batches</li> </ul>	33,700,000
76	 <b>DHI-NVR4116HS-I2</b> <span style="background-color: yellow; padding: 2px 5px;">4K</span> <span style="background-color: blue; padding: 2px 5px;">AI</span>	<p><b>"16 CH Compact 1U Network Video Recorder"</b></p> <ul style="list-style-type: none"> <li>New 4.0 user interface • 16 channel IP video access</li> <li>Smart H.265+/Smart H.264+/H.265/H.264/MJPEG; H.265 auto switch</li> <li>Up to 12MP resolution for live view and playback</li> <li>AI disabled: 1-channel 12MP@30 fps; 1-channel 8MP@30 fps; 2-channel 5MP@30 fps; 3-channel 4MP@30 fps; 6-channel 1080p@30 fps</li> <li>AI enabled: 1-channel 8MP@30 fps; 1-channel 5MP@30 fps; 2-channel 4MP@30 fps; 4-channel 1080p@30 fps</li> <li>200 Mbps for access, 200 Mbps for storage and 100 Mbps for forwarding</li> <li>2 channels Perimeter Protection by Camera, Search for pictures by channel, time and event type</li> <li>4 channels SMD Plus by Camera, Search by target classification (human, vehicle)</li> <li>1 channel face detection and recognition (AI by NVR); or 2-channel perimeter detection (AI by NVR); or 4-channel SMD (AI by NVR); up to 10 face databases and 5,000 face images</li> <li>1*HDMI, 1*VGA External Port, 1 front USB 2.0 port, 1 rear USB 2.0 port</li> <li>1 channel RCA connector Audio Input, 2 channels RCA connector, which supports voice intercom output</li> <li>1 SATA III ports, up to 16 TB for a single HDD</li> <li>ONVIF (profile T/S/G); CGI; SDK Network Interoperability</li> <li>Security baseline 2.1</li> </ul>	53,000,000



دستگاه ضبط تصویر تحت شبکه داهوا مدل DHI-NVR4108HS-4KS2/L



دستگاه ضبط تصویر تحت شبکه داهوا مدل DHI-NVR4116HS-I2

NO.	Model   Appearance	Specification	Price (IRR)
77	 <span style="background-color: yellow; padding: 2px 5px;">4K</span> <b>DHI-NVR4116HS-4KS2/L</b>	<p><b>"16 CH Compact 1U 1HDD Network Video Recorder"</b></p> <ul style="list-style-type: none"> <li>New 4.0 user interface, Security baseline 2.1</li> <li>H.264, H.265, Smart H.264+, and Smart H.265+. H.265 auto switch</li> <li><b>Max. decoding capability:</b> 8 × 1080p@30 fps. Supports adaptive decoding</li> <li>Supports mainstream cameras of ONVIF and RTSP protocols</li> <li>P2P remote surveillance, video play on mobile device</li> <li>VGA/HDMI simultaneous video output, maximum resolution of HDMI is 4K</li> <li><b>AI by Camera:</b> Face detection, perimeter protection, IVS, people counting, heat map, and SMD</li> <li>Supports remote configuration and management of IPC, such as setting parameters, getting information, and upgrading IPC of the same model in batches</li> <li>1 SATA III ports, up to 10 TB for a single HDD</li> </ul>	50,500,000
78	 <span style="background-color: yellow; padding: 2px 5px;">4K</span> <b>DHI-NVR4216-4KS2/L</b>	<p><b>"16 Channel 1U 2HDDs Network Video Recorder"</b></p> <ul style="list-style-type: none"> <li>New 4.0 user interface, Security baseline 2.1</li> <li>H.264, H.265, Smart H.264+, and Smart H.265+. H.265 auto switch</li> <li><b>Max. decoding capability:</b> 8 × 1080p@30 fps. Supports adaptive decoding</li> <li>Supports mainstream cameras of ONVIF and RTSP protocols</li> <li>P2P remote surveillance, video play on mobile device</li> <li>VGA/HDMI simultaneous video output, maximum resolution of HDMI is 4K</li> <li><b>AI by Camera:</b> Face detection, perimeter protection, IVS, people counting, heat map, and SMD</li> <li>Supports remote configuration and management of IPC, such as setting parameters, getting information, and upgrading IPC of the same model in batches</li> <li>2 SATA III ports, up to 10 TB for a single HDD</li> </ul>	67,000,000



دستگاه ضبط تصویر تحت شبکه داهوا مدل DHI-NVR4116HS-4KS2/L



دستگاه ضبط تصویر تحت شبکه داهوا مدل DHI-NVR4216-4KS2/L

NO.	Model   Appearance	Specification	Price (IRR)
79	 <b>DHI-NVR4232-4KS2/L</b>	<p><b>4K</b></p> <p>“32 CH 1U 2HDDs Network Video Recorder”</p> <ul style="list-style-type: none"> <li>New 4.0 user interface, Security baseline 2.1</li> <li>H.264, H.265, Smart H.264+, and Smart H.265+. H.265 auto switch</li> <li><b>Max. decoding capability:</b> 8 × 1080p@30 fps. Supports adaptive decoding</li> <li>Supports mainstream cameras of ONVIF and RTSP protocols</li> <li>P2P remote surveillance, video play on mobile device</li> <li>VGA/HDMI simultaneous video output, maximum resolution of HDMI is 4K</li> <li><b>AI by Camera:</b> Face detection, perimeter protection, IVS, people counting, heat map, and SMD</li> <li>Supports remote configuration and management of IPC, such as setting parameters, getting information, and upgrading IPC of the same model in batches</li> <li>2 SATA III ports, up to 10 TB for a single HDD</li> </ul>	82,000,000
80	 <b>DH-NVR4432-4KS2/I</b> <b>Wiz Sense</b>	<p><b>AI</b></p> <p>“32 Channel 1.5U 4HDDs WizSense Network Video Recorder”</p> <ul style="list-style-type: none"> <li>Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format</li> <li>Access, storage or forwarding at 256 Mbps (160 Mbps when function enabled)</li> <li>Max. decoding capability: 10 × 1080p@30 fps. Supports adaptive decoding</li> <li>AI by NVR: 1-channel face detection and recognition; 2-channel perimeter protection; up to 10 face databases and 20,000 face images; 4-channel SMD Plus</li> <li>AI by Camera: Face detection and recognition, perimeter protection; SMD Plus; ANPR; people counting; stereo analysis; heat map</li> <li>Security baseline 2.1</li> <li>4 SATA ports, up to 10 TB. The maximum HDD capacity varies with environment temperature</li> </ul>	160,000,000


NO.	Model   Appearance	Specification	Price (IRR)
81	 <b>DHI-NVR5432-4KS2</b> 	<p>“32 Channel 1.5U 4HDDs 4K &amp; H.265 Pro Network Video Recorder</p> <ul style="list-style-type: none"> <li>• New 4.0 user interface</li> <li>• 32channel IP video access</li> <li>• Smart H.265+/Smart H.264+/H.265/H.264/MJPEG; H.265 auto switch</li> <li>• Up to 24MP resolution for live view and playback</li> <li>• 16-channel@1080P (30 fps) decoding capacity</li> <li>• 320 Mbps for access, 320 Mbps for storage and 320 Mbps for forwarding</li> <li>• 20 channels Perimeter Protection by Camera, Search for pictures by channel, time and event type</li> <li>• 14 channels Face Recognition by Camera, Search for pictures by channel, time and face attributes</li> <li>• 32 channels SMD Plus by Camera, Search by target classification (human, vehicle)</li> <li>• 4 channels ANPR by Camera, 16 channels Stereo Analysis by Camera</li> <li>• 2*HDMI, 2*VGA External Port, 1 front USB 2.0 port, 2 rear USB 3.0 ports</li> <li>• 1 channel RCA connector Audio Input, 2 channels RCA connector, which supports voice intercom output</li> <li>• 4 SATA III ports, up to 10 TB for a single HDD, 1 eSATA Support</li> <li>• 1-channel fisheye dewarping (AI by NVR)</li> <li>• ONVIF (profile T/S/G); CGI; SDK Network Interoperability</li> </ul>  دستگاه ضبط تصویر تحت شبکه داهوا مدل DHI-NVR5432-4KS2	200,000,000
82	 <b>DHI-NVR5232-4KS2</b> 	<p>“32Channel 1U 4K&amp;H.265 Pro Network Video Recorder”</p> <ul style="list-style-type: none"> <li>• Smart H.265+/H.265/H.264+/H.264/MJPEG decoding</li> <li>• Max 320Mbps incoming bandwidth, Up to 12Mp resolution preview &amp; playback</li> <li>• Max 4-ch@8MP(30fps), 16-ch@1080P(30fps) decoding</li> <li>• 1*HDMI(4K)/1*VGA simultaneous video output</li> <li>• 2*SATA HDDs(10 TB for each HDD), 2 USB(1 USB3.0,1 USB2.0)</li> <li>• 1*1000 Mbps Network Card, RS232, RS485, 4/2 Alarm In/out, P2P Support</li> <li>• AI by Camera: Perimeter protection; face detection and recognition; SMD Plus; video metadata; ANPR; people counting; stereo analysis; crowd distribution; heat map</li> </ul>  دستگاه ضبط تصویر تحت شبکه داهوا مدل DHI-NVR5232-4KS2	129,000,000

NO.	Model   Appearance	Specification	Price (IRR)
83	 <b>DH-NVR5464-4KS2</b> 	<p><b>4K AI</b></p> <p>64 Channel 1.5U 4HDDs 4K &amp; H.265 Pro Network Video Recorder"</p> <ul style="list-style-type: none"> <li>Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding</li> <li>Max 320Mbps incoming bandwidth, Up to 12Mp resolution preview &amp; playback</li> <li>Max 4-ch@8MP(30fps), 16-ch@1080P(30fps) decoding</li> <li>2*HDMI/2*VGA simultaneous video output</li> <li>4*SATA HDDs(10TB for each HDD), 3 USB(2 USB3.0,1 USB2.0)</li> <li>Support 1 e-SATA, 2*1000 Mbps Network Card, RS232, RS485, 16/6 Alarm In/out, P2P Support</li> <li>AI by Camera: Perimeter protection; face detection and recognition; SMD Plus; video metadata; ANPR; people counting; stereo analysis; crowd distribution; heat map</li> </ul>	223,000,000
84	 <b>DHI-NVR5816-4KS2</b> 	<p><b>4K AI</b></p> <p>"16 CH 2U 8HDDs 4K &amp; H.265 Pro Network Video Recorder"</p> <ul style="list-style-type: none"> <li>16channel IP video access</li> <li>New 4.0 user interface</li> <li>Smart H.265+/Smart H.264+/H.265/H.264/MJPEG; H.265 auto switch</li> <li>Up to 24MP resolution for live view and playback</li> <li>16-channel@1080P (30 fps) decoding capacity</li> <li>320 Mbps for access, 320 Mbps for storage and 320 Mbps for forwarding</li> <li>16 channels Perimeter Protection by Camera,Search for pictures by channel, time and event type</li> <li>14 channels Face Recognition by Camera, Search for pictures by channel, time and face attributes</li> <li>16 channels SMD Plus by Camera, Search by target classification (human, vehicle)</li> <li>4 channels ANPR by Camera, 16 channels Stereo Analysis by Camera</li> <li>2*HDMI, 2*VGA External Port, 1 front USB 2.0 port, 2 rear USB 3.0 ports</li> <li>1 channel RCA connector Audio Input, 2 channels RCA connector, which supports voice intercom output</li> <li>8 SATA III ports, up to 10TB for a single HDD, 1 eSATA Support</li> <li>1-channel fisheye dewarping (AI by NVR)</li> <li>ONVIF(profile T/S/G); CGI; SDK Network Interoperability</li> </ul>	CALL

NO.	Model   Appearance	Specification	Price (IRR)
85	<b>DHI-NVR5832-4KS2</b>  <span>4K</span> <span>AI</span> 	<p>“32CH 2U 8HDDs 4K &amp; H.265 Pro Network Video Recorder”</p> <ul style="list-style-type: none"> <li>• 64channel IP video access</li> <li>• Smart H.265+/Smart H.264+/H.265/H.264/MJPEG; H.265 auto switch</li> <li>• Up to 24MP resolution for live view and playback</li> <li>• 16-channel@1080P (30 fps) decoding capacity</li> <li>• 320 Mbps for access, 320 Mbps for storage and 320 Mbps for forwarding</li> <li>• 20 channels Perimeter Protection by Camera,Search for pictures by channel, time and event type</li> <li>• 14 channels Face Recognition by Camera, Search for pictures by channel, time and face attributes</li> <li>• 64 channels SMD Plus by Camera, Search by target classification (human, vehicle)</li> <li>• 4 channels ANPR by Camera, 16 channels Stereo Analysis by Camera</li> <li>• 2*HDMI, 2*VGA External Port, 1 front USB 2.0 port, 2 rear USB 3.0 ports</li> <li>• 1 channel RCA connector Audio Input, 2 channels RCA connector, which supports voice intercom output</li> <li>• 8 SATA III ports, up to 10 TB for a single HDD, 1 eSATA Support</li> <li>• 1-channel fisheye dewarping (AI by NVR)</li> <li>• ONVIF(profile T/S/G); CGI; SDK Network Interoperability</li> </ul> <p> دستگاه ضبط تصویر تحت شبکه داهوا مدل DHI-NVR5832-4KS2</p>	257,000,000
86	<b>DHI-NVR5864-4KS2</b>  <span>4K</span> <span>AI</span> 	<p>“64 CH 2U 8HDDs 4K &amp; H.265 Pro Network Video Recorder”</p> <ul style="list-style-type: none"> <li>• 64channel IP video access • New 4.0 user interface</li> <li>• Smart H.265+/Smart H.264+/H.265/H.264/MJPEG; H.265 auto switch</li> <li>• Up to 24MP resolution for live view and playback</li> <li>• 16-channel@1080P (30 fps) decoding capacity</li> <li>• 320 Mbps for access, 320 Mbps for storage and 320 Mbps for forwarding</li> <li>• 20 channels Perimeter Protection by Camera,Search for pictures by channel, time and event type</li> <li>• 14 channels Face Recognition by Camera, Search for pictures by channel, time and face attributes</li> <li>• 64 channels SMD Plus by Camera, Search by target classification (human, vehicle)</li> <li>• 4 channels ANPR by Camera, 16 channels Stereo Analysis by Camera</li> <li>• 2*HDMI, 2*VGA External Port, 1 front USB 2.0 port, 2 rear USB 3.0 ports</li> <li>• 1 channel RCA connector Audio Input, 2 channels RCA connector, which supports voice intercom output</li> <li>• 8 SATA III ports, up to 10 TB for a single HDD, 1 eSATA Support</li> <li>• 1-channel fisheye dewarping (AI by NVR)</li> <li>• ONVIF(profile T/S/G); CGI; SDK Network Interoperability</li> </ul> <p> دستگاه ضبط تصویر تحت شبکه داهوا مدل DHI-NVR5864-4KS2</p>	340,000,000

NO.	Model   Appearance	Specification	Price (IRR)
87	<b>DHI-NVR608-32-4KS2</b>  <span>4K</span> <span>AI</span> 	<p>“32 CH 2U 8HDDs Ultra series Network Video Recorder”</p> <ul style="list-style-type: none"> <li>• New 4.0 user interface • 32channel IP video access</li> <li>• Smart H.265+/Smart H.264+/H.265/H.264/MJPEG; H.265 auto switch</li> <li>• 384 Mbps for access, 384 Mbps for storage and 384 Mbps for forwarding</li> <li>• 24 channels Perimeter Protection by Camera,Search for pictures by channel, time and event type</li> <li>• 24 channels Face Recognition by Camera, Search for pictures by channel, time and face attributes</li> <li>• 32 channels SMD Plus by Camera, Search by target classification (human, vehicle)</li> <li>• 8 channels ANPR by Camera, 32 channels Stereo Analysis by Camera</li> <li>• 8 SATA III ports, up to 10 TB for a single HDD, 1 eSATA Support</li> <li>• Multiple data mode such as Raid0, Raid1, Raid5, Raid6, and Raid10</li> <li>• Remote configuration and management of IPCs, such as setting pa rameters, acquiring information and upgrading IPCs of the same model in batches</li> <li>• AI-by-camera functions such as perimeter protection, face detection and recognition, SMD Plus, video metadata, ANPR and 3D behavior analysis</li> <li>• N+M cluster. When the host fails, the standbydevice will continue to record; once the host recovers,video recorded on the standby device will be transmitted back</li> <li>• ONVIF(profile T/S/G); CGI; SDK Network Interoperability</li> </ul> <p> دستگاه ضبط تصویر تحت شبکه داهوا مدل DHI-NVR608-32-4KS2</p>	273,000,000
88	<b>DHI-NVR608-64-4KS2</b>  <span>4K</span> <span>AI</span> 	<p>“64 Ch 2U 8HDDs Ultra series Network Video Recorder”</p> <ul style="list-style-type: none"> <li>• New 4.0 user interface • 64channel IP video access</li> <li>• Smart H.265+/Smart H.264+/H.265/H.264/MJPEG; H.265 auto switch</li> <li>• 384 Mbps for access, 384 Mbps for storage and 384 Mbps for forwarding</li> <li>• 24 channels Perimeter Protection by Camera,Search for pictures by channel, time and event type</li> <li>• 24 channels Face Recognition by Camera, Search for pictures by channel, time and face attributes</li> <li>• 32 channels SMD Plus by Camera, Search by target classification (human, vehicle)</li> <li>• 8 channels ANPR by Camera, 32 channels Stereo Analysis by Camera</li> <li>• 8 SATA III ports, up to 10 TB for a single HDD, 1 eSATA Support</li> <li>• Multiple data mode such as Raid0, Raid1, Raid5, Raid6, and Raid10</li> <li>• Remote configuration and management of IPCs, such as setting pa rameters, acquiring information and upgrading IPCs of the same model in batches</li> <li>• AI-by-camera functions such as perimeter protection, face detection and recognition, SMD Plus, video metadata, ANPR and 3D behavior analysis</li> <li>• N+M cluster. When the host fails, the standbydevice will continue to record; once the host recovers,video recorded on the standby device will be transmitted back</li> <li>• ONVIF(profile T/S/G); CGI; SDK Network Interoperability</li> </ul> <p> دستگاه ضبط تصویر تحت شبکه داهوا مدل DHI-NVR608-64-4KS2</p>	485,000,000

NO.	Model   Appearance	Specification	Price (IRR)
89	<b>DHI-NVR608-128-4KS2</b>  <span>4K</span> <span>AI</span>	<p>“128CH 2U 8HDDs Ultra series Network Video Recorder”</p> <ul style="list-style-type: none"> <li>• New 4.0 user interface</li> <li>• 128channel IP video access</li> <li>• Smart H.265+/Smart H.264+/H.265/H.264/MJPEG; H.265 auto switch</li> <li>• 384 Mbps for access, 384 Mbps for storage and 384 Mbps for forwarding</li> <li>• 24 channels Perimeter Protection by Camera,Search for pictures by channel, time and event type</li> <li>• 24 channels Face Recognition by Camera, Search for pictures by channel, time and face attributes</li> <li>• 32 channels SMD Plus by Camera, Search by target classification (human, vehicle)</li> <li>• 8 channels ANPR by Camera, 32 channels Stereo Analysis by Camera</li> <li>• 8 SATA III ports, up to 10 TB for a single HDD, 1 eSATA Support</li> <li>• Multiple data mode such as Raid0, Raid1, Raid5, Raid6, and Raid10</li> <li>• Remote configuration and management of IPCs, such as setting parameters, acquiring information and upgrading IPCs of the same model in batches</li> <li>• AI-by-camera functions such as perimeter protection, face detection and recognition, SMD Plus, video metadata, ANPR and 3D behavior analysis</li> <li>• N+M cluster. When the host fails, the standby device will continue to record; once the host recovers,video recorded on the standby device will be transmitted back</li> <li>• ONVIF(profile T/S/G); CGI; SDK Network Interoperability</li> </ul> <p> دستگاه ضبط تصویر تحت شبکه داهوا مدل DHI-NVR608-128-4KS2</p>	540,000,000
90	<b>NKB1000</b> 	<p>“Network Keyboard Controller”</p> <ul style="list-style-type: none"> <li>• Dahua High Speed Dome</li> <li>• Dahua Standalone DVR</li> <li>• Network Video Server</li> <li>• Connection: RS485, RS422 (reserved), USB, RS232 &amp; Network</li> <li>• Functions: <ul style="list-style-type: none"> <li>• Three Dimensional Joystick Control of PTZ Functions</li> <li>• Preset Position, Auto Scan, Auto Pan, Auto Tour &amp; Pattern Auxiliary Functions</li> <li>• On-Screen Menu &amp; User Operation Procedure Tips</li> <li>• Connect to SmartPSS or DSS platform via USB</li> </ul> </li> </ul> <p> دستگاه ضبط تصویر تحت شبکه داهوا مدل NKB1000</p>	89,250,000



مشتری گرامی؛

با تشکر از حسن انتخاب شما؛

جهت فعالسازی و اطلاع از مدت زمان گارانتی کافیست  
به سایت پرارین به آدرس [perarinco.com](http://perarinco.com) مراجعه کنید.

همچنین جهت بهره مندی از خدمات پشتیبانی ۲۴ ساعته  
پرارین با شماره تماس ۰۲۱-۹۱۳۰۴۰۰۳ حاصل فرمایید.

**Perarin  
24 +6  
ماه گارانتی**